

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MAY 4 7 44 AM '95

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

Name of Operator

Mallon Oil Company

Address and Telephone No.

P.O. Box 3256, Carlsbad, NM 88220 (505) 885-4596

Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL and 860' FEL (SE NE) Unit H
Sec. 34, T19S-R34E

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-052

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Mallon 34 Federal No. 7

9. API Well No.

30-025-32782

10. Field and Pool, or Exploratory Area

Delaware

11. County or Parish, State

Lea County, New Mexico

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other TD/Production Casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on well completion or Recompletion Report and Log forms.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

2/15/95: start drilling 8-3/4" hole from 1512' to 5520'. 2/27/95: drill 7-7/8" hole from 5520' to 6300' (TD). Ran 5-1/2" x 17# and 15.5# casing to 6300'. Stage 1 - cement with 155 sacks Class C + 5# CSE + 5/10% CF-14 + 5# salt + 5# Gilsonite + 1/4# Celloseal. Second stage - cement with 1150 sacks Pacesetter Lite + 5# salt + 1/4# Celloseal followed by 250 sacks Class C + 5# CSE + 5/10% CF-14 + 5# salt + 5# Gilsonite + 1/4# Celloseal. Circulate 11 sacks cement to surface. Plug down at 4:30 am 3/3/95.

J. Lara
7 1995

I hereby certify that the foregoing is true and correct

Signed

Title Production Superintendent

Date 3/5/95

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side