

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

P.O. Box 1980  
Hobbs, NM 88241

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a well, recompletion, or other well operations.  
Use "APPLICATION FOR PERMIT -" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other:

2. Name of Operator

Mallon Oil Company

3. Address and Telephone No.

P.O. Box 3256, Carlsbad, NM 88220 (505) 885-4596

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL and 660' FWL (NW SW) Unit L  
Sec. 34, T19S-R34E

5. Lease Designation and Serial No.  
NM-052

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.  
Mallon 34 Federal No. 16

9. Well API No.  
30-025-32818

10. Field and Pool, or Exploratory Area  
NE Lea Delaware

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment ☐ Change of Plans  
☐ Recompletion ☐ New Construction  
☐ Plugging Back ☐ Non-Routine Fracturing  
☐ Casing Repair ☐ Water Shut-Off  
☐ Altering Casing ☐ Conversion to Injection  
☒ Other: Spud/Surface Cag ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)

Mallon Oil Company spudded 14-3/4" hole at 8:00 am 11/8/96. Drilled to 1485'. Ran 9-5/8" x 36# casing to 1485'. Cemented with 650 sks 65/35 POZ CaCl2 followed by 200 sks Class C + 2% CaCl2 PD at 8:40 pm 11/13/96. Did not circulate cement to surface. Ran temperature log - cement top 28' from surface. RIH with 1". Pump 128 sks Class C + 2% CaCl2. Circulate 50 sks to surface.

NOV 27 1996

RECEIVED

NOV 27 10 34 AM '96

*DC Winkler*

14. I hereby certify that the foregoing is true and correct.

Signed Duane C. Winkler

Title Production Superintendent Date 11-19-96

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved B \_\_\_\_\_

Title \_\_\_\_\_ Date \_\_\_\_\_

Conditions of approval, if any:

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side