

District
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address. Bonneville Fuels Corporation 1660 Lincoln St., Suite 1800 Denver, Colorado 80264		² OGRID Number 2678
		³ API Number 30 - 025-32919
⁴ Property Code 2158 <i>LY</i>	⁵ Property Name Lottie York	⁶ Well No. #4

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	14	17S	37E		2080'	South	750'	West	Lea

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
R-10295 11/19/96 South									
⁹ Proposed Pool 1 South Humble City: Strawn						¹⁰ Proposed Pool 2			

¹¹ Work Type Code N	¹² Well Type Code O	¹³ Cable/Rotary R	¹⁴ Lease Type Code P	¹⁵ Ground Level Elevation 3744'
¹⁶ Multiple No	¹⁷ Proposed Depth 11,750'	¹⁸ Formation Atoka Shale	¹⁹ Contractor	²⁰ Spud Date Est. 8-1-95

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17 1/2"	13 3/8"	54.5	450'	475 sx.	Surface
11"	8 5/8"	32.0	4,750'	1,050 sx.	Surface
7 7/8"	5 1/2"	17.0	11,750'	1st: 545 sx.	8,775'
				2nd: 510 sx.	4,450'
				Stage Tool @ 8	775'

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Drill 17-1/2" hole to 450'. Set & cement 13-3/8" casing (w/475 sx. cmt.) to surface. Install BOPE. Pressure test to 1000 PSIG. Drill 11" hole to 4,750'. Set & cement 8-5/8" intermediate casing (w/1,050 sx. cmt.) to isolate upper Permian salts and anhydrites & to provide well control prior to drilling deep oil and gas bearing formations. Test BOPE and casing to 2500 PSIG. Drill 7-7/8" hole to 11,750' to evaluate Strawn Fm. Run DST in Strawn Fm. and log 7-7/8" hole. Run 5-1/2" casing & cement to 4,450' (w/1,055 sx. cmt. in 2 stages w/Tool @ 8,775') if warranted. Otherwise, P&A well as directed by State of New Mexico.

A well plan, including BOPE specification, is attached for your information.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *Robert A. Schwering*
Printed name: Robert A. Schwering, P.E.
Title: Senior Engineer
Date: April 7, 1995
Phone: (303) 863-1555

OIL CONSERVATION DIVISION

Approved by: **ORIGINAL SIGNED BY**

Title: **GARY WINK**
FIELD REP. II

Approval Date: **APR 11 1995**

Expiration Date:

Conditions of Approval:

Attached ☐

Permit Expires 6 Months From Approval
Date Unless Drilling Underway.

mp

APR 11 1985
FIELD REP. II
CARY WINK
ORIGINAL SIGNED BY

RECEIVED

APR 11 1985
OFFICE

EIGHT POINT DRILLING PLAN

Attached to Form C-101:

Operator: Bonneville Fuels Corporation

Lottie York #4

2080' FSL & 750' FWL

Section 14, T.17S., R.37E. N.M.P.M.

Lea County, New Mexico

1. ESTIMATED TOPS: IMPORTANT GEOLOGIC MARKERS:

Permian:

Red Beds:	Surface
Anhydrites & Red Beds:	1700'
Anhydrites, Salts & Shales:	2200'
Anhydrites & Shales:	3600'
Seven Rivers Fm.:	4700'
Queen Fm.:	5125'
Grayburg Fm.	5260'
San Andres Fm.	5545'
Glorieta Fm.	7020'
Yeso Fm.	7219'
Tubb Fm.	8101'
Lower Clearfork Fm.	8400'
3rd Bone Springs Fm.	9435'
Abo Fm.	9765'
Wolfcamp Group	9895'
Wolfcamp Detrital	10945'

Pennsylvanian:

Canyon Fm.	11260'
Strawn Fm.	11355'
Lower Strawn	11605'
Atoka Fm.	11680'

2. ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS:

Fresh Water: Occ. Surface Sands: Surface to 400'.

Oil and Gas Targets:	Strawn Fm.:	11355'.
	Lower Strawn:	11605'.

Possible Gas and Oil:	Tubb Fm.:	8101'.
	Lower Clearfork Fm.:	8400'.
	Wolfcamp Fm.:	9895'.

PROJECTED TOTAL DEPTH: 11,750'.

RECEIVED

APR 1 1963

COMMUNICATIONS
OFFICE

3. MINIMUM SPECS FOR PRESSURE CONTROL:

a. A diagram of the Blowout Preventer Stack and Wellhead Equipment is presented in Exhibit #1. The wellhead equipment for the intermediate hole (11" @ 4750') is altered only by the replacement of the 13-5/8" 3000 psi WP x 11" 5000 psi WP cross-over spool with the 13-5/8" 3000 psi WP x 11" 5000 psi WP casing spool during the drilling of the 7-7/8" production hole. A diagram of the Choke Manifold is presented in Exhibit #2. All BOP and Choke Manifold equipment will be rated to 5000 psi WP(min).

b. Surface Casing Wellhead Equipment will consist of:

- i. A 13-5/8" slip-on weld-on 3000 psi WP(min) braiden head w/ 2: 2" SE outlets with 2: 2" SE XXHVY Nipples and 2: 2" SE FO 3000 psi WP(min) ball valves. This braiden head will be welded on & nipples up after the 450' 13-3/8" Surface Casing is set and cemented.
- ii. A 13-5/8" 3000 psi WP(min) x 11" 5000 psi WP(min) cross-over spool will be installed upon the braiden head. This spool will be removed when the 8-5/8" Protective Casing has been set and cemented.
- iii. All wellhead and BOP equipment and the 13-3/8" surface casing will be pressure tested to 1000 psi with the rig pumps prior to drilling out.

c. Protective Casing Wellhead Equipment will consist of:

- i. A 13-5/8" slip-on weld-on 3000 psi WP(min) braiden head w/ 2: 2" SE outlets with 2: 2" SE XXHVY Nipples and 2: 2" SE FO 3000 psi WP(min) ball valves.
- ii. A 13-5/8" 3000 psi WP x 11" 5000 psi WP casing spool w/ 2: 2" FO FE outlets w/ 2: 2" FO FE 5000 psi WP gate valves. This casing spool will be nipples up after the 4750' 8-5/8" protective casing is set and cemented. The secondary seal will be tested to 1500 psi.
- iii. All wellhead and BOP equipment and the 8-5/8" protective casing will be pressure tested to 2500 psi prior to drilling out.

RECEIVED

Aug 11 1985

U.S. MARSHALS
OFFICE

3. MINIMUM SPECS FOR PRESSURE CONTROL (CONTINUED):

- d. The BOP Equipment, nipped up on the 13-5/8" 3000 psi x 11" 5000 psi cross-over spool for the 11" intermediate hole, and the 13-5/8" 3000 psi x 11" 5000 psi casing spools for the 7-7/8" production hole, will be as follows:
- i. An 11" Nom. 5000 psi WP(min) mud cross with a 2" 5000 psi WP(min) FO FE kill-side inlet and a 4" 5000 psi WP(min) FO FE choke-side outlet.
 - ii. An 11" Nom. 5000 psi WP(min) double gate (or dual equivalent single gate) hydraulic ram-type preventer with Pipe Rams over Blind Rams. Pipe rams are anticipated to be 4-1/2".
 - iii. An 11" Nom. 5000 psi WP(min) hydraulic annular (bag-type) preventer.
 - iv. A choke manifold consisting of a 4"(min nom) x 5,000 psi WP(min) FE choke/bloody line between the 2: 4" 5000 psi WP(min) FO FE master gate valves at the wellhead and the choke manifold 2 x 4" and 2 x 2" 5000 psi WP(min) cross with a 4" 5000 psi WP(min) FO FE ball/gate valve downstream of the cross. Between the downstream 4" ball/gate valve and the manifold cross will be a 4" x 4" x 2" 5000 psi WP(min) FO FE tee with a 2" 5000 psi WP(min) FO FE ball/gate valve with a 2" 5000 psi WP(min) Gauge Assembly for monitoring pressure at the choke manifold. The choke manifold will have 2: 2" 5000 psi FO FE ball/gate valves between the manifold cross and the 2: 2" FO FE 5000 psi(min) adjustable chokes (a total of 4: 2" 5000 psi ball/gate valves - 2 on each wing). Provision may be made to tie in DST surface lines to the choke manifold thru an optional 2" 5000 psi WP(min) FO FE tee above the 2" 5000 psi WP(min) ball/gate valve downstream of the choke manifold cross. The 4" bloody line downstream of the choke manifold will be staked down and targeted in the flare pit. The 2: 2" lines downstream of the chokes will be appropriately fixed or staked down to return mud to the pits, oil to test tanks, gas/oil cut mud to a separator or test tank, and gas to a flare pit.
 - v. A 5000 psi WP(min) FO safety valve and a 5000 psi WP(min) dart valve, with drill pipe threads and subs to meet other drill string threads, will be kept on the drill floor after the 13-3/8" surface casing is set. A 5000 psi(min) WP Upper kelly valve and a 5000 psi WP(min) Lower kelly valve will be kept on the kelly throughout drilling operations. All valves, and the wrenches to operate these valves, will be maintained on the floor in good order throughout drilling operations.

3. MINIMUM SPECS FOR PRESSURE CONTROL (CONTINUED):

d. The BOP Equipment (Continued):

- vi. An accumulator with sufficient capacity to operate the BOPE against a 3000 psi well pressure(min) will be used to operate the BOP system. It shall contain double the fluid capacity calculated to open and close the pipe rams, blind rams, and annular preventer 1 time each, and then to close the pipe rams and annular preventer 1 additional time(min) and retain accumulator pressure at 200 psig over the pre-charge pressure. The accumulator working pressure shall be 1,500 psi(minimum) with a pre-charge pressure between 700-800 psi(minimum). A Nitrogen bottle system shall provide independent (reserve) power to operate the system in the event rig motors must be shut down.

e. The testing procedures and frequency are as follows:

- i. For the 13-3/8" surface casing nipple-up and prior to drilling the 11" intermediate hole:
ALL of the pressure side BOP Equipment specified in Part d. above will be nipped-up on the surface casing and each component will be hydraulically tested for ten(10) minutes(min) to 1000 psi and five(5) minutes(min) to 300 psi prior to drilling out cement. Pipe rams will be operationally checked each 24 hour period, and the blind rams operationally checked each time pipe is pulled from the hole. These pressure tests and function tests will be noted and described on the daily drilling report. After the float collar is drilled out of the surface casing (prior to drilling out the shoe) the surface casing will be pressure tested to 1,000 psi for thirty(30) minutes(min).
- ii. For the 8-5/8" intermediate casing nipple-up and prior to drilling the 7-7/8" production hole:
ALL of the pressure side BOP Equipment specified in Part d. above will be nipped-up on the casing spool and each component will be hydraulically tested for ten(10) minutes(min) to 2500 psi and five(5) minutes(min) to 250 psi prior to drilling out cement. The Pipe rams will be operationally checked each 24 hour period, and the blind rams operationally checked each time pipe is pulled from the hole. These pressure tests and function tests will be noted and described on the daily drilling report. After the float collar is drilled out of the intermediate casing, and prior to drilling out the shoe, the intermediate casing will be pressure tested to 2,500 psi for thirty(30) minutes(min). The surface BOP equipment will be pressure tested every 30 operating days after the pressure test at protective casing nipple-up.

3. MINIMUM SPECS FOR PRESSURE CONTROL (CONTINUED):

f. Tripping procedures for well control:

i. For the 11" intermediate hole:

A mud weight of 9.5 PPG is anticipated at a depth of 2450' and a mud weight of 10.4 PPG is anticipated at a depth of 4750' (Total Depth for this interval). The well will be drilled by a triple-derrick rig (92' avg. length per stand). The well will be monitored each 5 stands to insure that the BHA is not swabbing the well in. The well will be filled after each 20 stands of drill pipe, 3 stands of 6-1/2" drill collars, and as each stand of large outside diameter drill collars (7" O.D. or larger) are pulled from the hole. Pits will be monitored in order to insure that the well is taking fluid on trips. **In the event that the bit is plugged on a trip the well will be filled after each 7 stands of drill pipe are pulled from the well and as each stand of drill collars are pulled from the well. Swabbing will be checked each 3 stands.**

ii. For the 7-7/8" production hole:

The anticipated maximum bottom-hole formation pressure is 3690 psig at 9,895' (Wolfcamp) and 3670 psig at 11,355' (Strawn). The anticipated mud weight in this interval is 8.4 to 9.5 PPG. This will provide a minimum hydrostatic pressure of 4320 psig (630 psig overbalance) at the Wolfcamp and 4960 psig (1290 psig overbalance) at the Strawn. The well will be drilled by a triple-derrick rig (92' avg. length per stand). The well will be monitored each 5 stands to insure that the BHA is not swabbing the well in. The well will be filled after each 20 stands of drill pipe and as each stand of drill collars are pulled from the hole. Pits will be monitored in order to insure that the well is taking fluid on the trip. **In the event that the bit is plugged on a trip the well will be filled after each 5 stands of drill pipe are pulled from the well and as each stand of drill collars are pulled from the well. Swabbing will be checked each 3 stands.**

g. Procedures for running production casing:

Prior to running production casing the hole will be filled. The blind rams will be closed and the well will be monitored for flow while a set 5.5" casing rams will be installed in the BOP to replace the pipe rams. Casing will then be run and cemented. The BOPE will remain nipped up UNTIL the well is cemented.

4. CASING AND CEMENTING PROGRAM:

a. The Proposed Casing Program:

- i. Surface Casing:
13-3/8" O.D. 54.5#/ft. J-55 8rd. ST&C: Surface to 450'.
- ii. Intermediate Casing:
8-5/8" O.D. 32#/ft. HCK-55 8rd. LT&C: Surface to 40'.
8-5/8" O.D. 32#/ft. K-55 8rd. LT&C: 40' to 3100'.
8-5/8" O.D. 32#/ft. HCK-55 8rd. LT&C: 3100' to 4750'.
- iii. Production Casing:
5-1/2" O.D. 17#/ft. N-80 8rd. LT&C: Surface to 2950'.
5-1/2" O.D. 17#/ft. K-55 8rd. LT&C: 2950' to 7300'.
5-1/2" O.D. 17#/ft. N-80 8rd. LT&C: 7300' to 11750'.

b. The Proposed Cementing Program:

- i. Surface Casing: Single Stage:
Est. 75 F. @ 9.5 PPG mud @ 450'.
Circ. Cement to Surface:
100% excess over calculated volume.
Top job required if cement does not circulate.
475 sx. Class 'C' w/ 2% CaCl₂ + 0.25 #/sx. cellophane:
1.33 cu.ft./sx. @ 14.8 PPG.
- ii. Intermediate Casing: Single Stage:
Est. 115 F. @ 10.4 PPG mud @ 4750'.
Plan Circ. Cement to Surface:
Temp. Survey & Possible Top Job If Cement Does NOT Reach
Surface Casing @ 450'.
Lead Slurry: Est. Surface to 4450'.
130 % excess over calculated volume: Est. @
920 sx. Lite (65% Class 'C' + 35% Pozzalan + 6% Gel)
w/ 3% Sodium Meta-Sillicate + 15 #/sx. NaCl +
0.25 #/sx. cellophane + Additives:
2.76 cu.ft./sx. @ 11.8 PPG.
Tail Slurry: Est. 4450' to 4750'.
100 % excess over calculated volume: Est. @
130 sx. Class 'C' w/ 2% CaCl₂ + 0.25 #/sx. cellophane +
Additives:
1.33 cu.ft./sx. @ 14.8 PPG.

4. CASING AND CEMENTING PROGRAM (CONTINUED):

b. The Proposed Cementing Program (Continued):

- iii. Production Casing: Two Stage: Stage Tool @ 8775':
ALL VOLUMES TO BE BASED ON CALIPER LOG VOLUMES.

First Stage: Est. 180 F. @ 9.2 PPG mud @ 11750'.

Plan Circ. Cement to 8775':

Lead Slurry: Est. 9175' to 8775'.

100 % excess over calculated volume: Est. @

60 sx. Lite (65% Class 'H' + 35% Pozzalan + 6% Gel)
w/ 12 #/sx. NaCl + 3 #/sx. KCl + Additives.

2.30 cu.ft./sx. @ 11.4 PPG.

Tail Slurry: Est. 11750' to 9175':

40 % excess over calculated volume: Est. @

485 sx. 50% Class 'H' + 50% Pozzalan + 2% Gel
w/ 3 #/sx. KCl + Additives.

1.30 cu.ft./sx. @ 14.2 PPG.

Second Stage: Est. 150 F. @ 9.2 PPG mud @ 8775':

Lead Slurry: Est. 4450' to 7800':

60 % excess over calculated volume: Est. @

325 sx. Lite (65% Class 'C' + 35% Pozzalan + 6% Gel)
w/ 3% Sodium Meta-Sillicate + 15 #/sx. NaCl +

0.50 #/sx. cellophane + Additives:

2.76 cu.ft./sx. @ 11.8 PPG.

Tail Slurry: Est. 7800' to 8775':

40 % excess over calculated volume: Est. @

185 sx. 50% Class 'H' + 50% Pozzalan + 2% Gel
w/ 3 #/sx. KCl + Additives.

1.30 cu.ft./sx. @ 14.2 PPG.

5. PROPOSED DRILLING FLUIDS:

The reserve pit will be constructed in two segments & will be fully lined with a minimum 12 mil thickness plastic liner to protect the surface environment and fresh water resources.

- a. 17-1/2" Surface Hole: Surface to 450': Fresh Water Spud Mud:
Additives: Gel, Lime & LCM as needed to maintain circulation.
Est. 9.0 to 9.5 PPG @ VIS 40 to 120 sec./qt.
- b. 11" Intermediate Hole: Circulate the Reserve Pit Brine Section.
 - i. 450' to 2450': Native Mud: Fresh Water & Native Solids:
Additives: Possible Gel sweeps & LCM as needed to maintain circulation and clean the hole.
Est. 8.4 to 9.5 PPG @ VIS 30 to 34 sec./qt.
 - ii. 2450' to 4750': Native Mud: Saturated Brine & Native Solids:
Additives: Possible Attapulgate Gels, Fresh Water Gels to sweep and clean the hole, field crude oil to reduce mud weight, shale sloughing and differential sticking, and LCM as needed to maintain circulation.
Est. 9.5 to 10.4 PPG @ VIS 32 to 35 sec./qt.
- c. 7-7/8" Production Hole:
 - i. 4750' to 9775': Native Mud: Fresh Water & Native Solids:
Circulate the Reserve Pit Fresh Water Mud Section.
Additives: Possible Fresh Water Gels to sweep and clean the hole, field crude oil and/or diesel to reduce mud weight, shale sloughing and differential sticking, and LCM as needed to maintain circulation.
Est. 8.34 to 8.5 PPG @ VIS 28 - 30 sec./qt.
 - ii. 9775' to 11750': Low Solids Slightly Dispersed:
Circulate in Mud Tanks.
Additives: Fresh Water Gel, Drispac, Soda Ash, Ben-Ex, Starch, and KCl w/ LCM as necessary to maintain circulation and stabilize shales with soltex and/or diesel if required for differential sticking.
Est. 8.8 to 9.5 PPG @ PV 5-22 cp., YP 5-21 pphsf., and VIS @ 34 - 45 sec./qt.

RECEIVED

APR 11 1995

CLERK OF COURTS
OFFICE

6. LOGGING, TESTING, AND CORING PROGRAM:


- a. The logging program will consist of:
 - i. DILL/SFL - GR/SP (Induction Logs):
T.D. to Intermediate Casing.
 - ii. LDT/CNL - GR/CAL (Density/Neutron Porosity Logs):
T.D. to Intermediate Casing.
 - iii. BHC Sonic - GR/CAL (Sonic Porosity and Travel Time Logs):
T.D. to Intermediate Casing.
- b. No cores are planned.
- c. A drill stem test is planned in the Upper Strawn Porosity:
Anticipated Pressure = approx. 3670 PSIG
Equiv. Mud Density @ 6.22 PPG @ 11,355'.
- d. Samples will be analyzed on-site by a geologist in order to determine total depth (T.D.) of the well. 30' samples (wet) to the base of the intermediate casing (4750'). 10' samples (wet & dry) from the base of the intermediate casing to T.D.

7. ABNORMAL CONDITIONS - PRESSURE - TEMPERATURE - POTENTIAL HAZARDS:


- a. Surface Hole to 450':
Normal pressures (fresh water gradient or less) and temperatures (70 F. to 75 F.) are anticipated for this hole segment.
- b. Intermediate Hole from 450' to 4750':
Saturated brine pressures (saturated salt water gradient @ 10.4 PPG: 0.54 PSI/ft.) and normal temperatures (75 F. to 115 F.) are anticipated for this hole segment. No H2S is anticipated.
- c. Production Hole from 4750' to 11750':
Subnormal pressures (less than the fresh water gradient @ 8.34 PPG: 0.434 PSI/ft.) and normal temperatures (115 F. to 180 F.) are anticipated for this hole segment. No H2S is anticipated.


8. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS:

This proposed location is an Orthodox proposed location. Location construction may be commenced in July after a surface damage agreement is reached with the surface owner, and damages are paid. Bonneville Fuels Corporation is desirous of drilling, completing, and producing at the Lottie York #3 location (in order to evaluate potential reservoir depletion) in the E 1/2 of the SW 1/4 of Section 14 (spud planned on April 26, 1995) PRIOR TO spudding this proposed well. As currently planned this well will be spud on approximately October 1, 1995 and drilled to a projected T.D. @ 11,750' in the Atoka Shale. Est. 32 drilling days. Est. 10 completion days. Est. 1st production on or after November 10, 1995.


 4/2/95
Robert A. Schwering, P.E.
Senior Engineer
Bonneville Fuels Corporation

LOTTIE YORK #4
MINIMUM BLOW-OUT PREVENTER REQUIREMENTS
ALL 5000 PSI WP EQUIPMENT
(Except Casinghead & Spools as noted below)





VICINITY MAP



SCALE: 1" = 2 MILES

SEC. 14 TWP. 17-S RGE. 37-E

SURVEY N.M.P.M.

COUNTY Lea STATE N. M.

DESCRIPTION 2080' FSL & 750' Fw1

ELEVATION 3744

OPERATOR Bonneville Fuels Corp.

LEASE Lottie York


JOHN WEST ENGINEERING
HOBBS, NEW MEXICO
(505) 393-3117

RECEIVED

APR 11 1966

OFFICE

LOCATION VERIFICATION MAP



SCALE: 1" = 2000'

CONTOUR INTERVAL 5'

SEC. 14 TWP. 17-S RGE. 37-E

SURVEY N.M.P.M.

COUNTY Lea STATE N. M.

DESCRIPTION 2080' FSL & 750' FWL.

ELEVATION 3744

OPERATOR Bonneville Fuels Corp.

LEASE Lottie York No. 4

U.S.G.S. TOPOGRAPHIC MAP
Humble City, N. Mex.

JOHN WEST ENGINEERING
HOBBS, NEW MEXICO
(505) 393-3117

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Artec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised February 10, 1994
Instruction on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-025-32919	Pool Code 33500	Pool Name South Humble Cith: Strawn
Property Code 2158 <i>IX</i>	Property Name LOTTIE YORK	Well Number 4
OGRID No. 2678	Operator Name BONNEVILLE FUELS CORP.	Elevation 3744


Surface Location

UL or lot No. L	Section 14	Township 17 S	Range 37 E	Lot Idn	Feet from the 2080	North/South line SOUTH	Feet from the 750	East/West line WEST	County LEA
--------------------	---------------	------------------	---------------	---------	-----------------------	---------------------------	----------------------	------------------------	---------------

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres 79.96		Joint or Infill	Consolidation Code	Order No.					

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify the the information
contained herein is true and complete to the
best of my knowledge and belief.

Robert A. Schwerling
Signature

Robert A. Schwerling, P.E.
Printed Name

Sr. Engineer @ BFC
Title

April 4, 1995
Date

SURVEYOR CERTIFICATION

I hereby certify that the well location shown
on this plat was plotted from field notes of
actual surveys made by me or under my
supervision, and that the same is true and
correct to the best of my belief.

FEBRUARY 15, 1995

Date Surveyed JLP

Signature of Professional Surveyor

Robert A. Schwerling
No. 32919

V.O. Num. 95-10-0248

Certificate No. JOHN W. WEST 676
RONALD J. EIDSON 3239

RECEIVED

11 1945

OFFICE