

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO. 30-025-32935
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. 16969
7. Lease Name or Unit Agreement Name Pearl State
8. Well No. 1
9. Pool name or Wildcat Pearl Queen
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3720 GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator Stevens & Tull, Inc.	
3. Address of Operator P.O. Box 11005, Midland, TX 79702	
4. Well Location Unit Letter <u>E</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>West</u> Line Section <u>36</u> Township <u>19S</u> Range <u>34E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3720 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☒
	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/11/97 - Plug and abandon well bore

Perfs: (5232' - 5240') - Bull plugged Loker set packer at 5200' - unable to retrieve
Perfs: (4888' - 5050') - CIBP set at 4800' - 3 sx cement on top
Perfs: (4533' - 4675') - CIBP set at 4500' - 3 sx cement on top
Perfs: (4090' - 4100') - CIBP set at 4060'
Perfs: (3960' - 3970') - 100 sx cement plug set at 3900'
Top of salt (1900') - 75 sx cement plug set at 1950'
Surface Plug - 10 sx cement plug set at 60'

Plugging procedure approved by Gary Wink on 7/10/97

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Michael G. Mooney TITLE Consulting Engineer DATE 7/14/97
TYPE OR PRINT NAME Michael G. Mooney TELEPHONE NO. 915/699-1410

(This space for State Use)

APPROVED BY Gary W. Wink OIL & GAS INSPECTOR DATE 7/14/97
CONDITIONS OF APPROVAL, IF ANY: