

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33333
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	B-155-1

WELL COMPLETION OR RECOMPLETION REPORT AND LOG								
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐					7. Lease Name or Unit Agreement Name CENTRAL VACUUM UNIT			
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐								
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.					8. Well No. 179			
3. Address of Operator 205 E. Bender, HOBBS, NM 88240					9. Pool Name or Wildcat VACUUM GRAYBURG SAN ANDRES			
4. Well Location Unit Letter L : 1997 Feet From The SOUTH Line and 1263 Feet From The WEST Line Section 36 Township 17S Range 34E NMPM LEA COUNTY								
10. Date Spudded 4/3/96	11. Date T.D. Reached 4/10/96	12. Date Compl. (Ready to Prod.) 4/21/96	13. Elevations (DF & RKB, RT, GR, etc.) 3999' GR	14. Elev. Csghead 3999'				
15. Total Depth 4850'	16. Plug Back T.D. 4850'	17. If Mult. Compl. How Many Zones?	18. Intervals Drilled By 0-4850'	Rotary Tools	Cable Tools			
19. Producing Interval(s), of this completion - Top, Bottom, Name 4340'-4720' (VACUUM GRAYBRUG SAN ANDRES)					20. Was Directional Survey Made YES			
21. Type Electric and Other Logs Run DLL-SDL-DSN, BHC-SONIC, GR-CAL, GR-CL-CBL					22. Was Well Cored NO			
23. CASING RECORD (Report all Strings set in well)								
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED			
8 5/8"	24#	1545'	11"	CL-C 550 SX, CIRC 100				
5 1/2"	15.5#	4850'	7 7/8"	CL-H 1000 SX, CIR 167				
24. LINER RECORD			25. TUBING RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET	
					2 3/8"	4350'		
26. Perforation record (interval, size, and number) 4340'-51', 4358'-67', 4379'-4420', 4439'-47', 4504'-11', 4514'-24', 4540'-46', 4596'-4603', 4609'-24', 4633'-53', 4662'-77', 4691'-4713', 4720'-45' (229', .45", 366 HLES)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
			DEPTH INTERVAL				AMOUNT AND KIND MATERIAL USED	
			4340'-4546'				ACID - 9500 GALS 15% NEFE HCL	
			4596'-4745'				ACID - 9500 GALS 15% NEFE HCL	
28. PRODUCTION								
Date First Production 4/21/96		Production Method (Flowing, gas lift, pumping - size and type pump) PUMPING- SUBMERSIBLE PUMP				Well Status (Prod. or Shut-in) PROD		
Date of Test 4/26/96	Hours tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 97	Gas - MCF 62	Water - Bbl. 1270	Gas - Oil Ratio 639	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API -(Corr.) 38.6		
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD						Test Witnessed By ODIS HENLEY		
30. List Attachment DEVIATION SURVEY								
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.								
SIGNATURE		TITLE			DATE			
Monte C. Duncan		Engr Asst			4/29/96			
TYPE OR PRINT NAME					Telephone No. 397-0418			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1487'	T. Canyon
T. Salt	1599'	T. Strawn
B. Salt	2623'	T. Atoka
T. Yates	2913'	T. Miss
T. 7 Rivers	3137'	T. Devonian
T. Queen	3727'	T. Silurian
T. Grayburg	4046'	T. Montoya
T. San Andres	4317'	T. Simpson
T. Glorieta		T. McKee
T. Paddock		T. Ellenburger
T. Blinberry		T. Gr. Wash
T. Tubb		T. Delaware Sand
T. Drinkard		T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 4253' to 4850'

No. 2, from to

No. 3, from to

No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1487'	1487'	SS, SHALE				
1487'	1599'	112'	ANHYDRITE				
1599'	2623'	1024'	SALT				
2623'	2913'	290'	ANHYDRITE, DOLOMITE				
2913'	4051'	1138'	ANHYDRITE, DOLO, SALT				
4051'	4850'	799'	ANHYDRITE, DOLO, LIME				