

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-025-33582
5. Indicate Type of Lease
STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
19490

7. Lease Name or Unit Agreement Name

STATE -27-

8. Well No.

1

9. Pool name or Wildcat

Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER Dry

2. Name of Operator

Henry Petroleum Corp.

3. Address of Operator

3525 Andrews Hwy. - Suite 200 - Midland TX 79703-5048

4. Well Location

Unit Letter K : 1650 Feet From The South Line and 1980 Feet From The West Line

Section 27

Township

17-S

Range

35-E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3936' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Plug Back to 4800' & Transfer well to ☒

Phillips Petro. Co.

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

03/17/97 - Dumped 35 sx. on existing CIPB @ 11,780'
Set 5-1/2" CIPB @ 11,640'

03/18/97 - Circ. hole w/10# brine w/25# salt gel per bbl.
Spot 10 sx. plug on top of CIPB @ 11,640'
Pumped 30 sx. cement plug from 11,341' to 11,141'

Cut 5-1/2" casing @ 9,531' - casing not free

03/19/97 - Cut 5-1/2" casing @ 5,800' - lay down casing

03/20/97 - Spot 25 sx. cement plug from 9,631' to 9,431'

Spot 25 sx. cement plug from 8,250' to 8,050'

Spot 40 sx. cement plug from 5,850' to 5,700'

Spot 40 sx. cement plug from 4,900' to 4,800'

Turn well over to Phillips Petroleum Company.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Roy R. Johnson

TITLE

Regulatory & Materials Tech.

DATE

03/25/97

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY
GARY WINK
FIELD REP. II

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 31 1997

