

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.	30-025-33582
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	19490

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name STATE -27-	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	8. Well No. 1		
2. Name of Operator HENRY PETROLEUM CORP.	9. Pool name or Wildcat Wildcat - Devonian/Morrow		
3. Address of Operator 3525 Andrews Hwy. - Suite 200 - Midland TX 79703-5048			
4. Well Location Unit Letter K : 1650 Feet From The South Line and 1980 Feet From The West Line Section 27 Township 17-S Range 35-E NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3936' GR		

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/06/96: TD 13,000' - Set 30 sx. 50/50 Poz cement plug 12,812' to 12,712' to Plug Back above Devonian zone to Morrow Zone.
11/07/96: TD 13,000' - PBDT 12,043' - Ran & set 302 jts. of 5-1/2" M-95 & N-80 LT&C casing & set at 12,043' - Cemented 5-1/2" casing w/460 sx. 50/50 Poz, 2% gel, 2% D-112 & 3% KCl - Displaced w/278 bbls. 3% KCl water - Had good returns - Plug down @ 6:30 AM 11/06/96 - Nipple down - Set slips - Cleaned pits - Released rig @ 10:00 AM 11/06/96 - Ran Temp. survey - Found top of cement at 10,745'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy R. Johnson TITLE Regulatory & Materials Tech. DATE 11/11/96

TYPE OR PRINT NAME ROY R. JOHNSON

915-694-3000

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JUDY SEXTON
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

DATE

NOV 15 1996