

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-33583

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
MARALO, INC.

3. Address of Operator
P. O. BOX 832, MIDLAND, TX 79702

7. Lease Name or Unit Agreement Name

BURROWS 17

8. Well No.
1

9. Pool name or Wildcat
WILDCAT

4. Well Location
Unit Letter A : 870 Feet From The NORTH Line and 1180 Feet From The EAST Line
Section 17 Township 17S Range 38E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3702'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/02/96 SPUD WELL @ 7:00 AM. DRILLED 17-1/2" HOLE TO 492'. RU & RUN 11 JTS 13-3/8" 48# H-40 ST6C CSG. SET @ 492'. CEMENT CSG W/495 SXS PREM. PLUS CLASS "C" CEMENT W/2# CACL2. CEMENT CIRCULATED TO SURFACE. WOC 8.5 HRS. NU BOP & TEST TO 1000# (2.5 HRS). DRILLED PLUG & CEMENT.

12/11/96 DRILLED 11" HOLE, DEPTH OUT 5020'. REC'D VERBAL APPROVAL FROM NMCD/JERRY SEXTON/HOBBS TO CHANGE SETTING DEPTH OF 8-5/8" CSG FROM 5500' (PERMITTED DEPTH) TO +/- 5000'. RU & RAN 116 JTS 8-5/8" 32# CSG. SET @ 5020'. CEMENT 8-5/8" CSG, LEAD W/1200 SXS PREM PLUS LITE W/3# GILSONITE + 1/4# FLOCELE. TAIL W/200 SXS PREM PLUS CL. "C" W/1# CACL2. CEMENT CIRCULATED TO SURFACE. ND & WOC.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dorothea Logan TITLE REGULATORY ANALYST DATE DECEMBER 12, 1996

TYPE OR PRINT NAME DOROTHEA LOGAN

TELEPHONE NO. (915) 684-7441

(This space for State Use)

APPROVED BY Geologist TITLE Geologist DATE DEC 16 1996

CONDITIONS OF APPROVAL, IF ANY: