

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**DISTRICT I**  
P.O. Box 1980, Hobbs, NM 88240

**DISTRICT II**  
P.O. Drawer 110, Artesia, NM 88210

**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-33757

5. Indicate Type of Lease

STATE ☒

FEE

6. State Oil & Gas Lease No.

VA-1188

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

TMBR/Sharp Drilling, Inc.

3. Address of Operator

P. O. Drawer 10970, Midland, TX 79702

4. Well Location

Unit Letter G : 1750 Feet From The North Line and 2100 Feet From The East

Section 1 Township 19S Range 35E NMPM Lea Co.

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3845 GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDON ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

01/08/97 MIRU TMBR/Sharp Rig #17.

01/09/97 Spudded well 01/09/97 @ 11:30 PM CST.

01/11/97 Ran 44 jts (1878') 8-5/8" 24# J-55 STC csg & set @ 1872'. Cmt w/636 sx Hal. Lite Prem Plus containing 6% salt 1/4#/sk Celloflake mixed with fresh wtr @ 12.4 ppg. Tail w/275 sx Prem Plus containing 2% CaC2, 1/4#/sk Celloflake mixed with fresh wtr @ 14.8 ppg. Displaced csg with 116 BBL fresh wtr with Howco pump in 18 min. Bumped plug with 1000 psi. PD @ 2:45 PM 01-11-97. Had 100% returns. Circ 125 sx. Used 10 centralizers spaced middle shoe jt w/lock ring, 1st collar every 3rd collar.

01/12/97 Resumed drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Engineering Manager

DATE 1/14/97

TYPE OR PRINT NAME

Jeff Phillips

(915) 699-5050

TELEPHONE NO.

(This space for State Use)

JAN 16 1997