

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1649'	T. Canyon
T. Salt	1758'	T. Strawn
B. Salt	2770'	T. Atoka
T. Yates	2964'	T. Miss
T. 7 Rivers	3277'	T. Devonian
T. Queen	3940'	T. Silurian
T. Grayburg	4363'	T. Montoya
T. San Andres	4673'	T. Simpson
T. Glorieta	6119'	T. McKee
T. Paddock	6215'	T. Ellenburger
T. Blinbry	6508'	T. Gr. Wash
T. Tubb	7478'	T. Delaware Sand
T. Drinkard	7720'	T. Bone Springs
T. Abo	8192'	T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 8645' to 8860'

No. 2, from to

No. 3, from to

No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	1544'	1544'	SS, Shale				
1544'	1695'	151'	Anhydrite				
1695'	2700'	1005'	Salt				
2700'	2870'	170'	Dolomite, Anhydrite				
2870'	4475'	1605'	Dol, Anhy, SS				
4475'	8175'	3700'	Dol, SS, LS				
8175'	8950'	775'	Dol, LS, Shale				