

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-34422

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Louis Dreyfus Natural Gas Corp.

3. Address of Operator

14000 Quail Springs Parkway, Suite 600, Oklahoma City, OK 73134

7. Lease Name or Unit Agreement Name

Toro 21 State Com

8. Well No.

1

9. Pool name or Wildcat

Wildcat Devonian

4. Well Location

Unit Letter H : 2310 Feet From The North Line and 660 Feet From The East Line

Section 21

Township 19S

Range 35E

NMPM Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3752' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Sidetracking ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12 1/4" hole from 656' to 5085'. Twisted off, unable to recover fish from 4469' - 4619' (5-6 1/2 drill collars) and fish at 4561', btm. @ 5085' (C bit, SS, 1-8" DC, stab, 9-8" DC, X-O, 7- 6 1/2" DC). Spotted cement from 4454' to 3715', cemented with 700 sxs. Class H cmt. w/9/10% CD 31 (18 ppg .9u). Tagged TOC @ 3888'. Wash cmt. f/3888' to 3918'. Drilled cmt. from 3918' - 3938'. Drilled f/3938' - 3980' with 7 3/4", 2 1/2 deg. bent sub. Laydown motor; drilled 3980'-4018', 10% cmt, 90% Anhy; drill 4018'-4112', 5% cmt, 95% form.; drill 4112'-4206', 60% cmt, 40% Anhy; drilled 4206'-4230', 100% cmt. PU 7 3/4" mud motor, 2.5 deg. bent sub and 8 3/4" monel collar, drill 4230'-4239', 80% cmt. Drill 4239'-4276', 65% cmt.

TD 4276', elected to plug. Notified New Mexico OCD of intent to plug 8/21/98.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Terrye D. Bryant

TITLE

Regulatory Technician

DATE 8/25/98

TYPE OR PRINT NAME

Terrye D. Bryant

(405) 749-5287
TELEPHONE NO.

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: