Submit 3 Copies to Appropriate District Office	State of New Mexico Energy,nerals and Natural Resources Department				Form C-103 Revised 1-1-89		
DISTRICT I	OIL CONSERVA	OIL CONSERVATION DIVISION					
P.O. Box 1960, Hobbs, NM 88240 2040 Pacheco S				WELL API NO.			
DISTRICT II. Santa Fe, NM 87505			05)-025-34520		
P.O. Drawer DD, Artesia, NM 88210				sindicate Type of Le	ase state		
<u>DISTRICT III</u> 1000 Rio Brazos Rd., Azlec, NM 87410)			oState Oll & Gas Lea		FEE	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				۲Lease Name or Unit Agreement Name Vacuum "18" State			
IType of Well: OIL GAS WELL WELL							
zName of Operator	Name of Operator				aWelt No.		
Mewbourne Oil Company				1 Pool name or Wildcat			
Address of Operator PO Box 5270, Hobbs, New Mexico 88240 (505)393-5905				Vacuum Atoka; Morrow, North (Gas)			
Well Location							
Unit Letter <u>H</u> : <u>16</u>	50 Feet From The North		Line and660	Feet From The	East	_ Line	
18 Section 1	7S Township 35E		nge	NMPM	Lea c	Sounty	
Indelevation (Show whether DF, RKB, RT, GR, etc.) 3992							
11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data							
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:							
						r1	
PERFORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WORK		ALTERING CASING	•	
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE DRILLING C			PNS.	PLUG AND ANBANI		
PULL OR ALTER CASING			CASING TEST AND CEMI	ENT JOB			
OTHER:			OTHER:			[]	
	erations (Clearly state all pertinent details, an	d give p	ertinent dates, including es	stimated date of startin	g any proposed		
work) SEE RULE 1103							
Spudded at 6:15/pm, 12-26-98 Drilled a 17 1/2" hole to 462' and set 13 3/8" 48# H40 ST&C AT 462'. Cemented with 440 sacks of Class "C" + 2% cc. Plug down at 6:30/am 12-27-98. Circulated 90 sacks to pits. Tested casing to 500 psi before drilling out.							
Drilled a 12 1/4" hole and set 9 5/8" 40# N80/J55 ST&L/LT&C AT 4826'. Cemented with 1385 sacks of (35:65) Poz. Class "C" + 5#/sack Salt + 6% Gel + 1/4# per sack Celloflake. Tialed with 200 sacks of Class 'C" + 1%cc. Plug was down at 2:15/pm, 01-06-99, Circulated 35 sacks to pits. Tested casing to 1500 psi before drilling out.							
	pove is true and complete to the best of my kr Matatuus ews	זודנו	e and bellef. E Drilling Superinten	dent	DATE 01-08-9 TELEPHONE NO. 393		
(This space for State Use) 引行的人	SUPED BY CHRIS WILLIAME						
ť	DISTRICT I SUPERVISOR						
APPROVED BY			E		DATE	<u> </u>	
CONDITIONS OF APPROVAL, IF ANY:							