

New Mexico Oil Conservation Division, DISTRICT 1  
1625 N. Beach Drive  
Hobbs, NM 88240

Form 3160-3  
(July 1992)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE  
(Other instructions on  
reverse side)

FORM APPROVED  
OMB NO. 1004-0136  
Expires: February 28, 1995

003

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK

DRILL ☒

DEEPEN ☐

b. TYPE OF WELL

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

SINGLE  
ZONE ☐

MULTIPLE  
ZONE ☐

2. NAME OF OPERATOR

Matador Operating Company

3. ADDRESS AND TELEPHONE NO.

8340 Meadow Rd., #158, Dallas, TX 75231, 214-987-7144

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface 1980 FNL-660 FWL

At proposed prod. zone same

E

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE

25 miles west of Hobbs

15. DISTANCE FROM PROPOSED  
LOCATION TO NEAREST  
PROPERTY OR LEASE LINE, FT.  
(Also to nearest drg. unit line, if any)

660'

16. NO. OF ACRES IN LEASE

1920

17. NO. OF ACRES ASSIGNED  
TO THIS WELL

320 ac

18. DISTANCE FROM PROPOSED LOCATION  
TO NEAREST WELL, DRILLING, COMPLETED,  
OR APPLIED FOR, ON THIS LEASE, FT.

2660'

19. PROPOSED DEPTH

13,750'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3586' GL

22. APPROX. DATE WORK WILL START

October 27, 1999

23. **P-111-P POTASH SECRETARY'S POTASH AND CEMENT CAPTAIN CONTROLLED WATER BASIN**

SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17-1/2"	13-3/8" H-40	48#	850'	
11"	8-5/8" J-55 & HCK-55	32#	5200	
7-7/8"	5-1/2" L-80 & S-95	17#	13,750	540 sx

Drill 13,750' Morrow/ Bone Spring test. Drill 17-1/2" hole to  $\pm 850'$ . Run and cement 13-3/8" casing to surface. Nu BOP stack and drill 11" hole to  $\pm 5200'$ . Run and cement 8-5/8" casing to surface. NU 5M BOP assembly and test. Drill 7-7/8" hole to  $\pm 13,750'$  and evaluate.

Well Location and Acreage Dedication Plat

Application for Permit to Drill (Drilling Program)

Surface Use Plan

Exhibit A, Area Map

Exhibit B, Wellsite Plan

Exhibit C, Production Map

Exhibit D, Blowout preventer requirements

Exhibit E, BOP schematic

Exhibit F, choke manifold

Well Plan Outline

Topo Map

**APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS  
ATTACHED**

IN ABOVE SPACE DESCRIBE PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

*J. W. Bell*

TITLE Drilling Manager

DATE

9-23-99

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

*Carsten F. Goff*

TITLE

ACTING STATE DIRECTOR

DATE

OCT 26 1999

\*See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

OPER. OGRID NO. 14245  
PROPERTY NO. 22437  
POOL CODE 77380  
EFF. DATE 11-1-99  
API NO. 30-025-34749

APPROVED FOR 1 YEAR  
mfp

SEP 29 1999

DISTRICT I  
P. O. Box 1980  
Hobbs, NM 88241-1980

State of New Mexico  
Energy, Minerals, and Natural Resources Department

Form C-102  
Revised 02-10-94  
Instructions on back

DISTRICT II  
P. O. Drawer DD  
Artesia, NM 88211-0719

OIL CONSERVATION DIVISION

P. O. Box 2088  
Santa Fe, New Mexico 87504-2088

Submit to the Appropriate  
District Office  
State Lease - 4 copies  
Fee Lease - 3 copies

☐ AMENDED REPORT

DISTRICT III  
1000 Rio Brazos Rd.  
Aztec, NM 87410

DISTRICT IV  
P. O. Box 2088  
Santa Fe, NM 87507-2088

WELL LOCATION AND ACREAGE DEDICATION PLAT

1 API Number <b>30-025-34749</b>	2 Pool Code 77380	3 Pool Name Gem E Morrow
4 Property Code 022437	5 Property Name <b>LAGUNA DEEP UNIT FEDERAL</b>	6 Well Number 5
7 OGRID No. 014245	8 Operator Name MATADOR OPERATING COMPANY	9 Elevation 3586'

10 SURFACE LOCATION


UL or lot no. E	Section 35	Township 19 SOUTH	Range 33 EAST, N.M.P.M.	Lot Ida	Feet from the 1980'	North/South line NORTH	Feet from the 660'	East/West line WEST	County LEA
--------------------	---------------	----------------------	----------------------------	---------	------------------------	---------------------------	-----------------------	------------------------	---------------

11 BOTTOM HOLE LOCATION IF DIFFERENT FROM SURFACE

UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County
---------------	---------	----------	-------	---------	---------------	------------------	---------------	----------------	--------

12 Dedicated Acres 320 ac	13 Joint or Infill	14 Consolidation Code	15 Order No.
------------------------------	--------------------	-----------------------	--------------

NO ALLOWABLE WELL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN  
CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information  
contained herein is true and complete  
to the best of my knowledge and belief.

Signature

Printed Name

John W. Bell

Title

Drilling Manager

Date

9-24-99

SURVEYOR CERTIFICATION

I hereby certify that the well  
location shown on this plat was  
plotted from field notes of actual  
surveys made by me or under  
my supervision, and that the  
same is true and correct to the  
best of my belief.

Date of Survey

SEPTEMBER 7, 1999

Signature and Seal of  
Professional Surveyor

V. LYNN  
BEZNER  
NO. 7920

Certified Notary Public  
V. L. BEZNER P.R.S. #7920

IOR #65110 / 72 SW / V.H.R.

# APPLICATION FOR PERMIT TO DRILL

## MATADOR OPERATING CORPORATION

### LAGUNA DEEP UNIT FEDERAL #5

1980' FNL & 660' FWL

SEC. 35, T19S, R33E

LEA COUNTY, NEW MEXICO

In conjunction with Form 3160-3, Application for Permit to Drill, Matador Operating Company submits the following items of pertinent information in accordance with Onshore Oil and Gas Order Nos. 1 & 2, and with all other applicable federal and state regulations.

1. Geologic Name of Surface Formation:

Permian

2. Estimated Tops of Important Geological Markers:

	MD	Subsea
Upper Permian Yates	3161'	+ 445'
Upper Permian Seven Rivers	3378'	+ 228'
Lower Permian Delaware	5306'	-1700'
Lower Permian Bone Spring	8086'	-4480'
1st Bone Spring SS Mbr	9186'	-5580' +
2rd Bone Spring SS Mbr	9726'	-6120' +
3rd Bone Spring SS Mbr	10526'	-6920'
Lower Permian Wolfcamp Fm	10821'	-7215'
Lower Permian Wolfcamp "Chert"	10981'	-7375'
Upper Penn Cisco	11751'	-8145'
Upper Penn Canyon	11959'	-8353'
Upper Penn Strawn	12066'	-8460'
Lower Penn Atoka	12301'	-8695'
Lower Penn Atoka LS	12631'	-9025'
Lower Penn Morrow	12831'	-9225'
Middle Morrow Clastics	13031'	-9425' *
Lower Morrow	13396'	-9790' *
TD	13750'	

\* = Primary Reservoir Targets

+ = Secondary Reservoir Targets

3. Estimated Depths of Anticipated Fresh Water, Oil, or Gas:

Upper Permian Sands	0-300'	fresh water
1st Bone Spring SS Mbr	9186'	oil
2nd Bone Spring SS Mbr	9726'	oil
Middle Morrow Clastics	13,031'	gas
Lower Morrow	13,396'	gas

The ground water will be protected by setting 13-3/8" surface casing at 425' and circulating cement back to surface. The productive Morrow horizons will be protected by setting 5-1/2" production casing at TD with cement tied back to approximately 12000'. If Bone Spring or any other pay above the Morrow is productive, we will bring top of cement 500' above uppermost productive zone.

4. Proposed Casing Program:

<u>Hole Size</u>	<u>Interval</u>	<u>Casing OD</u>	<u>Description</u>
25"	0-40'	20"	Conductor
17-1/2"	0-425' <del>850'</del>	13-3/8"	48#, H-40, ST&C, New, R-3
11"	0-5200'	8-5/8"	32#, J-55 & HCK-55, LT&C, New, R-3
7-7/8"	4000-1,200'	5-1/2"	17#, L-80 LT&C, New, R-3
7-7/8"	11,200-13,750'	5-1/2"	17#, S-95, LT&C, New, R-3

Proposed Cement Program:

20" Conductor:	Ready-mix poured to surface.
13-3/8" Surface Casing:	Cemented to surface with 115 sx Permian Basin Filler Cement & 200 sx Class "C" +2% CaCl <sub>2</sub> tail. Float equipment: Texas Pattern shoe with an insert float valve above the shoe joint and 2 centralizers. The shoe and first collar will be welded. One plug will be used to displace cement.
8-5/8" Intermediate Casing:	Set stage tool at ±2500'. Cement first stage with 400 sx Interfill "C" & 200 sx Class "C" +2% CaCl <sub>2</sub> tail. Cement 2nd stage with 1400 sx Interfill "C" + 50 sx Class C + 2% CaCl <sub>2</sub> . Float equipment: Float shoe with a float collar 1 joint above the shoe joint and 12 centralizers. The shoe and float collar will be welded. One plug will be used to displace cement.
5-1/2" Production Casing:	Cement 1st Stage:- 550 sx Super Modified H w/ 0.4% CFR-3, 0.5% Halad 344, 1# salt & 5# Gilsonite. Cement 2nd Stage (If necessary) ±700 sx Interfill "H" w/ 5# gilsonite followed by 100 sx "H" neat.

5. Pressure Control Equipment:

The blowout preventer equipment (BOP) shown in Exhibits D & E will consist of a double ram-type (5000 psi WP) preventer and a bag-type (hydril) preventer (3000 psi WP). Both units will be hydraulically operated and the ram-type preventer will be equipped with blind rams on top and 4-1/2" drill pipe rams on bottom. Both BOP's will be nipped up on the 13-3/8" surface casing and used continuously until TD is reached. All BOP's and accessory equipment will be tested to 1000 psi before drilling out of surface casing. Before drilling out of intermediate casing, the ram-type BOP and accessory equipment will be tested to 5000 psi and the hydril to 70% of rated working pressure (2100 psi).

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and 3" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 5000 psi WP rating which is shown in Exhibit F.

6. Proposed Mud System:

The proposed mud system will be a combination of fresh water, brine, cut brine, and polymer gel. The depths and mud properties of the mud system are listed below.

<u>Depth</u>	<u>Type</u>	<u>Weight (ppg)</u>	<u>Viscosity (sec)</u>	<u>Waterloss (cc)</u>	<u>ph</u>
0- <del>425</del> <sup>850</sup>	Fresh Water	8.3-8.8	28-30	Not Critical	9-10
850 <del>425</del> -5200'	Brine Water	8.8-10.2	28-30	Not Critical	9-10
5200-12,900'	Cut Brine	8.5-9.0	28-30	Not Critical	9-10
12,900-13,750	Polymer/Gel	9.0-9.8	30-32	<10	9-10

Sufficient mud materials to maintain the above mentioned mud properties and meet minimum lost circulation and weight increase requirements will be kept at the location at all times.

7. Auxiliary Well Control and Monitoring Equipment:

- A kelly cock will be kept in the drill string at all times.
- A full opening drill pipe stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- A mud logging unit complete with H2S detector will be monitoring drilling penetration rate and hydrocarbon shows from 5200' to TD.

8. Drillstem Testing, Logging, and Coring Programs:

- Drillstem tests will be run based on shows encountered while drilling.
- No logs are planned for the 11" hole section. The electric logging program for the 7-7/8" hole sections will consist of GR-Dual Laterolog MLL-LSS and GR Compensated Neutron--LithoDensity from TD to intermediate casing. Selected sidewell cores and RFT's may be taken in zones of interest.
- No conventional coring is anticipated.

9. Abnormal Conditions, Pressures, Temperatures, & Potential Hazards:

No abnormal pressures and/or temperatures are anticipated. No hydrogen sulfide or other hazardous gases or fluids are known to exist in this area. Possible loss circulation zones are expected from 3400' to 4500'. Possible water flow at  $\pm 2500'$ .

10. Anticipated Starting Date and Duration of Operations:

The anticipated start date will be October 27, 1999. Once commenced, drilling operations should be completed in approximately 40 days. If the well is productive, another 30 days will be required for completion work and facility installation.

**SURFACE USE PLAN**  
**MATADOR OPERATING COMPANY**  
**PIPELINE DEEP FEDERAL COM "5" #1**  
1980' FNL, 660' FWL  
Sec 35, T19S, R33E  
LEA COUNTY, NEW MEXICO

1. EXISTING ROADS - Area map, Exhibit "A", is a reproduction of the appropriate part of the U.S.G.S. New Mexico 7-1/2 minutes quadrangle. Existing roads are shown on the exhibit and the road to be used on the referenced well is marked. All roads shall be maintained in a condition equal to that which existed prior to the start of construction.
  - A. Exhibit "A" shows the proposed exploratory well site as staked.
  - B. Directions: From Hobbs, travel West on Hwy 62 and go 0.4 miles past mile marker 76. Turn North on Smith Ranch Road and travel 2.7 miles. Turn Left at the first "Y" and then turn Left (SW) at intersection of three lease roads. Proceed down double-pole power line road for 1.0 mile and then turn Right and travel .50 miles until new location.
2. PLANNED ACCESS ROADS - Existing lease roads with an extension of approximately 1320' of new road from existing road.
3. LOCATION OF EXISTING WELLS ON A ONE-MILE RADIUS
  - A. Water wells - NA.
  - B. Disposal wells - NA.
  - C. Drilling wells - NA.
  - D. Producing wells - As shown on Exhibit "C".
  - E. Abandoned wells - As shown on Exhibit "C".
4. If upon completion, the well is a producer, Matador Operating Company will furnish maps or plats showing On Well Pad Facilities, and Off Well Pad Facilities (if needed) on a Sundry Notice before construction of these facilities starts.



5. LOCATION AND TYPE OF WATER SUPPLY

Water will be purchased locally from a private source and trucked over the access road or piped in flexible lines laid on top of the ground.

6. SOURCE OF CONSTRUCTION MATERIALS

If needed, construction materials will be obtained from the drill site's excavations, or from a local source. These materials will be transported over the access route as shown in Exhibit "A".

7. METHODS FOR HANDLING WASTE DISPOSAL.

- A.
  - 1. Drill cuttings will be disposed of in the reserve pit.
  - 2. Trash, waste paper, and garbage will be contained in a fenced trash trailer to prevent wind-scattering during storage. When the rig moves out, all trash and debris will be hauled to an approved land-fill site.
  - 3. Salts remaining after completion of the well will be picked up by the supplier, including broken sacks.
  - 4. Sewage from trailer houses will drain into holes with minimum depth of 10'00". These holes will be covered during drilling and back-filled upon completion. A "porta-john" will be provided for the rig crews. This will be properly maintained during the drilling operations and removed upon completion of the well.
  - 5. Chemicals remaining after completion of the well will be stored in the manufacturer's containers and picked up by the supplier.
- B. Remaining drilling fluids will be allowed to evaporate in the reserve pit until the pit is dry enough for back-filling. In the event drilling fluids will not be evaporated in a reasonable period of time, they will be transported by a tank truck to a state approved disposal site.

Water produced during testing of the well will be disposed of in the reserve pit. Oil produced during testing of the well will be stored in test tanks until sold and hauled from the site.

8. ANCILLARY FACILITIES

No camps or airstrips will be constructed.

9. WELL SITE LAYOUT

- A. Exhibit "B" shows the proposed well site layout.
- B. This exhibit indicates proposed location of the reserve pits and trash trailer.
- C. Mud pits in the active circulating system will be steel pits and the reserve pit is proposed to be unlined, unless subsurface conditions encountered during pit construction indicate that lining is needed for lateral containment of fluids.
- D. If needed, the reserve pit is to be lined with a poly-ethylene liner. The pit liner will be a minimum of 6 mils thick. The pit liner will extend a minimum of 2'00" over the reserve pit dikes where the liner will be anchored down.
- E. The reserve pit will be fenced on three sides with four strands of barbed wire during drilling and completion phases. The fourth side will be fenced after all drilling operations have ceased. If the well is a producer, the reserve pit fence will be torn down. The reserve pit and those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.

10. PLANS FOR RESTORATION OF SURFACE

Rehabilitation of the location and reserve pit will start in a timely manner after all drilling operations cease. The type of reclamation will depend on whether the well is a producer or dry hole.

In either event, the reserve pit will be allowed to dry properly, and fluid removed and disposed of in accordance with Article 7.B as previously noted. The pit area will then be levelled and contoured to conform to the original and surrounding area as closely as is possible. Drainage system, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstances to prevent inundation of the location pad and surface facilities. After the area has been shaped and contoured, topsoil from the soil pits will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with BLM standards.

Should the well be a producer, the previously noted procedures will apply to those areas which are not required for production facilities.

11. OTHER INFORMATION

- A. The area around the wellsite is flat and covered with various grasses.
- B. The surface use is grazing and the owner is Ken Smith, Inc., P. O. Box 764, Carlsbad, NM 88221.
- C. An archaeological study has been conducted for the location and road. The report will be submitted under separate cover.
- D. There are no buildings in the area.

12. OPERATOR'S REPRESENTATIVE

Matador Operating Company's field representative for contact regarding compliance with the Surface Use Plan is:

Before, during, and after construction:

John W. Bell

8340 Meadow Road #158

Dallas, TX 75231

Office: 214-987-7144

Res: 972-818-8778

Mobile: 214-507-0985


13. CERTIFICATION

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Matador Operating Company and its contractors/ subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Name: John W. Bell  
John W. Bell  
Drilling Manager

Date: 9-24-99

# VICINITY MAP



Primary highway, hard surface \_\_\_\_\_  
Secondary highway, hard surface \_\_\_\_\_

Light duty road, principal street, hard or improved surface \_\_\_\_\_  
Other road or street; trail \_\_\_\_\_

Description Sec 35, T19S, R33E  
Lea County, NM

Operator MATADOR OPERATING CO.

Lease Name & Well No. \_\_\_\_\_

Remarks: \_\_\_\_\_

30 mi SW of Hobbs

\_\_\_\_\_

\_\_\_\_\_

Scale in Miles:



This location has been very carefully staked on the ground according to the best official survey records, maps, and other data available to us.

Review this plat and notify us immediately of any possible discrepancy.

## TOPOGRAPHIC LAND SURVEYORS

(915) 682-1653 / (800) 767-1653

2903 N. Big Spring Street  
Midland, TX 79705

EXHIBIT "A"

AREA MAP






EXHIBIT "B"

# WELLSITE PLAN

Matador Operating Company  
 Laguna Deep Unit Federal #5  
 1980 FNL & 660 FWL  
 Sec 35, T29S, R33E  
 Lea County, New Mexico

Proposed New Road

WELL LOCATION AND LEASE ROAD IN  
SECTION 35, T-19-S, R-33-E, N.M.P.  
LEA COUNTY, NEW MEXICO






EXHIBIT C  
PRODUCTION MAP

Matador Operating Company  
Laguna Deep Unit Federal #5  
1980 FNL & 660 FWL  
Sec 35, T29S, R33E  
Lea County, New Mexico

## MINIMUM BLOWOUT PREVENTER REQUIREMENTS

5,000 psi Working Pressure

5 MWP

## Blowout Preventer Requirements

Matador Operating Company  
Laguna Deep Unit Federal #5  
1980 FNL & 660 FWL  
Sec 35, T29S, R33E  
Lea County, New Mexico


## STACK REQUIREMENTS

No.	Item	Min. I.D.	Min. Nominal
1	Flowline		
2	Fill up line		2"
3	Drilling nipple		
4	Annular preventer		
5	Two single or one dual hydraulically operated rams		
6a	Drilling spool with 2" min. kill line and 3" min choke line outlets		
6b	2" min. kill line and 3" min. choke line outlets in ram. (Alternate to 6a above.)		
7	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/>	3-1/8"	
8	Gate valve—power operated	3-1/8"	
9	Line to choke manifold		3"
10	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/>	2-1/16"	
11	Check valve	2-1/16"	
12	Casing head		
13	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/>	1-13/16"	
14	Pressure gauge with needle valve		
15	Kill line to rig mud pump manifold		2"

## OPTIONAL

16	Flanged valve	1-13/16"	
----	---------------	----------	--

CONFIGURATION A



## CONTRACTOR'S OPTION TO FURNISH:

1. All equipment and connections above bradenhead or casinghead. Working pressure of preventers to be 5,000 psi, minimum.
2. Automatic accumulator (80 gallon, minimum) capable of closing BOP in 30 seconds or less and, holding them closed against full rated working pressure.
3. BOP controls, to be located near drillers position.
4. Kelly equipped with Kelly cock.
5. Inside blowout preventer or its equivalent on derrick floor at all times with proper threads to fit pipe being used.
6. Kelly saver-sub equipped with rubber casing protector at all times.
7. Plug type blowout preventer tester.
8. Extra set pipe rams to fit drill pipe in use on location at all times.
9. Type RX ring gaskets in place of Type R.

## MEC TO FURNISH:

1. Bradenhead or casinghead and slide valves.


## GENERAL NOTES:

1. Deviations from this drawing may be made only with the express permission of MEC's Drilling Manager.
2. All connections, valves, fittings, piping, etc., subject to well or pump pressure must be flanged (suitable clamp connections acceptable) and have minimum working pressure equal to rated working pressure of preventers up through choke. Valves must be full opening and suitable for high pressure mud service.
3. Controls to be of standard design and each marked, showing opening and closing position.
4. Chokes will be positioned so as not to hamper or delay changing of choke beans. Replaceable parts for adjustable choke, other bean sizes, retainers, and choke wrenches to be conveniently located for immediate use.
5. All valves to be equipped with handwheels or handles ready for immediate use.

7. Handwheels and extensions to be connected and ready for use.
8. Valves adjacent to drilling spool to be kept open. Use outside valves except for emergency.
9. All seamless steel control piping (5000 psi working pressure) to have flexible joints to avoid stress. Hoses will be permitted.
10. Casinghead connections shall not be used except in case of emergency.
11. Do not use kill line for routine fill-up operations.



# BOP SCHEMATIC



Choke Manifold Requirement (5000 psi WP)




EXHIBIT E

BOP Schematic

Matador Operating Company  
Laguna Deep Unit Federal #5  
1980 FNL & 660 FWL  
Sec 35, T29S, R33E  
Lea County, New Mexico


MINIMUM CHOKE MANIFOLD  
3,000, 5,000 and 10,000 PSI Working Pressure

EXHIBIT F

3 MWP - 5 MWP - 10 MWP

Choke Manifold

Matador Operating Company  
Laguna Deep Unit Federal #5  
1980 FNL & 660 FWL  
Sec 35, T29S, R33E  
Lea County, New Mexico



MINIMUM REQUIREMENTS										
No.		3,000 MWP			5,000 MWP			10,000 MWP		
		I.D.	NOMINAL	RATING	I.D.	NOMINAL	RATING	I.D.	NOMINAL	RATING
1	Line from drilling spool		3"	3,000		3"	5,000		3"	10,000
2	Cross 3"x3"x3"x2"			3,000			5,000			
	Cross 3"x3"x3"x3"									10,000
3	Valves (1) Gate □ Plug □ (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
4	Valve Gate □ Plug □ (2)	1-13/16"		3,000	1-13/16"		5,000	1-13/16"		10,000
4a	Valves (1)	2-1/16"		3,000	2-1/16"		5,000	3-1/8"		10,000
5	Pressure Gauge			3,000			5,000			10,000
6	Valves Gate □ Plug □ (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
7	Adjustable Choke (3)	2"		3,000	2"		5,000	2"		10,000
8	Adjustable Choke	1"		3,000	1"		5,000	2"		10,000
9	Line		3"	3,000		3"	5,000		3"	10,000
10	Line		2"	3,000		2"	5,000		3"	10,000
11	Valves Gate □ Plug □ (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
12	Lines		3"	1,000		3"	1,000		3"	2,000
13	Lines		3"	1,000		3"	1,000		3"	2,000
14	Remote reading compound standpipe pressure gauge			3,000			5,000			10,000
15	Gas Separator		2'x5'			2'x5'			2'x5'	
16	Line		4"	1,000		4"	1,000		4"	2,000
17	Valves Gate □ Plug □ (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000

(1) Only one required in Class 3LL.

(2) Gate valves only shall be used for Class 10LL.

(3) Remote operated hydraulic choke required on 5,000 psi and 10,000 psi for drilling.

EQUIPMENT SPECIFICATIONS AND INSTALLATION INSTRUCTIONS


1. All connections in choke manifold shall be welded, studded, flanged or Cameron clamp of comparable rating.
2. All flanges shall be API 6B or 6BX and ring gaskets shall be API RX or BX. Use only BX for 10 MWP.
3. All lines shall be securely anchored.
4. Chokes shall be equipped with tungsten carbide seats and needles, and replacements shall be available.
5. Choke manifold pressure and standpipe pressure gauges shall be available at the choke manifold to assist in regulating chokes. As an alternate with automatic chokes, a choke manifold pressure gauge shall be located on the rig floor in conjunction with the standpipe pressure gauge.
6. Line from drilling spool to choke manifold should be as straight as possible. Lines downstream from chokes shall make turns by large bends or 90° bends using bull plugged tees.
7. Discharge lines from chokes, choke bypass and from top of gas separator should vent as far as practical from the well.

Well Name:	<u>Laguna Deep Unit Federal #5</u>	County:	<u>Lea</u>	State:	<u>NM</u>
Location:	<u>1980 FNL &amp; 770 FWL</u>	Est KB:		TD:	<u>13,750</u>
	<u>Sec 35, T19S, R33E</u>	GL:	<u>3586'</u>		

[illegible]

LAGUNA GATUNA QUADRANGLE  
NEW MEXICO  
7.5 MINUTE SERIES (TOPOGRAPHIC)  
SW/4 LAGUNA GATUNA 15' QUADRANGLE

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY



Matador Operating Company  
Laguna Deep Unit Fed #5  
1980 FNL & 660 FWL  
Sec 35, T19S, R33E  
Lea County, New Mexico

From Hobbs, travel West on Hwy 62 and go 0.4 miles past mile market 76. Turn North on Smith Ranch road and travel 2.7 miles. Turn Left at the first "Y" and then turn Left (SW) at intersection of three lease roads. Proceed down double-pole power line road for 1.0 mile and then turn Right and travel .50 miles to new location.

United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Roswell Office

2909 West Second Street

Roswell, New Mexico 88201

Statement Accepting Responsibility for Operations

Operator name: Matador Operating Company  
Street or box: 8340 Meadow Road, #158  
City, State: Dallas, TX  
Zip code: 75231

The undersigned accepts all applicable terms, conditions, stipulations, and restrictions concerning operations conducted on the leased land or portion thereof, as described below:


All in Section 35, T19S, R33E, Eddy County, New Mexico

Lease No.: NM27572  
Legal Description of Land: S/2 Section 35  
Lease No.: NM27573  
Legal Description of Land: NW of NE/4 and N/2 NW Section 35  
Lease No.: NM9824  
Legal Description of Land: S/2 NW/4, S/2 NE/4, NE of NE/4 Section 35

Formation(s) (if applicable):

Bond Coverage: (State if individually bonded or another's bond)  
Statewide

BLM Bond File No.: 29403

Authorized Signature: 

R. F. Burke

Title: Vice President

Date:

ELF: 2/8/2000  
ABOVE DATE DOES NOT  
INDICATE WHEN  
CONFIDENTIAL LOGS  
WILL BE RELEASED

4  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100