

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-34941
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Breckon AUI
8. Well No. 1
9. Pool name or Wildcat Knowles Wolfcamp, Southeast

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter I : 1980 Feet From The South Line and 660 Feet From The East Line Section 27 Township 17S Range 38E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3659' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Resume drilling, surface casing & cmt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole with rotary tools at 9:30 PM 3-25-2000.

TD 400'. Reached TD at 2:00 AM 3-26-2000. Ran 9 joints of 11-3/4" 42# H-40 (403.17') of casing set at 400'. 1-Texas Pattern notched guide shoe set at 400'. Insert float set at 355'. Cemented with 300 sacks of Class C Premium Plus with 2% CaCl2 (yield 1.34, weight 14.83). PD 7:15 AM 3-26-2000. Bumped plug to 500 psi, OK. Circulated 73 sacks. WOC. Nippled up and tested to 500 psi for 15 minutes, OK. Drilled out at 2:45 AM 3-27-2000. WOC 20 hours and 30 minutes. Reduced hole to 11". Resumed drilling. NOTE: Notified OCD-Hobbs of upcoming casing and cement job - no witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 15, 2000

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: