

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-34941

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Breckon AUI

1. Type of Well:
OIL WELL ☒

GAS WELL ☐

OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

8. Well No.
1

3. Address of Operator
105 South 4th St., Artesia, NM 88210

9. Pool name or Wildcat
Knowles Wolfcamp, Southeast

4. Well Location

Unit Letter I : 1980 Feet From The South Line and 660 Feet From The East Line

Section 27 Township 17S Range 38E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3659' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Intermediate casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3630'. Reached TD at 10:30 PM 3-29-2000. Ran 81 joints of 8-5/8" 32# J-55 (3633.64') of casing set at 3630'. 1-regular guide shoe set at 3630'. Float collar set at 3585'. Cemented with 800 sacks Interfill "C" and 1/4#/sack flocele (yield 2.46, weight 11.9). Tailed in with 250 sacks Premium Plus "C" with 2% CaCl2 (yield 1.32, weight 14.8). PD 11:15 AM 3-30-2000. Bumped plug to 850 psi, OK. Circulated 175 sacks. WOC. Nipped up and tested to 1000 psi for 15 minutes. Drilled out at 1:00 PM 3-31-2000. WOC 25 hours and 45 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE

April 15, 2000

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: