

TMBR/SHARP DRILLING, INC.
Angell Phillips "13" State No. 1
990' FSL & 990' FEL
Sec. 13, T-17S, R-35E
Lea County, NM

01/04/00 SITP & SICP 0 psi. RU swab, FL 400'. Rec 20' or 1% oil. RD swab. PU gas anchor, 2" x 1 1/2" x 24' RHBC pump, 3/4" & 7/8" new T-66 rods. GIH, space out. Load tbg w/2% KCL. Press to 500 psi, ok. Stroke w/rig to 500 psi, 6 strokes, ok. RD Pool Well Service. Secure well. Will set pumping unit 01/04/01.

Tubing Detail:

1 - jt 2 3/8" 4.7# J-55 tbg w/bull plug	31.68	7630.12
1 - 2 3/8" perf sub	4.10	
1 - 2 3/8" API SN	.12	7598.44
18 - jts 2 3/8" 4.7# J-55 tbg	564.66	
1 - 5 1/2" x 2 3/8" TAC	3.11	7030.67
222 - jts 2 3/8" 4.7# J-55 tbg		7025.65

Rob Detail:

1 - 1" x 16' gas anchor	16.00
1 - 2" x 1 1/2" x 24' RHBC pump	24.00
104 - 3/4" x 25' T-66 rods w/short guides	2600.00
106 - 3/4" x 25' T-66 rods w/4 guides per rod	2650.00
91 - 7/8" x 25' T-66 rods w/4 guides per rod	2275.00
3 - 7/8" pony rods (1 - 2', 1 - 6' & 1 - 8')	16.00
1 - 1 1/4" x 26' polish rod w/16' x 1 1/2" liner	