State of New Mexico Submit 3 Copies to Appropriate Form C-103 District Office Minerals and Natural Resources Ene: Revised March 25, 1999 DISTRICT WELL AFI NO. 1625 n. French Dr., Hobbs, NM 88240 DISTRICT II OIL CONSERVATION DIVISION 30-025-35634 811 South First, Artesia, NM 88210 Indicate Type of Lease 2040 South Pacheco DISTRICT III STATE X FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 State Oil & Gas Lease No. DISTRICT IV 2040 S. Pacheco, Santa Fe, NM 87505 E--7277 SUNDRY NOTICES AND REPORTS ON WELLS Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS) Toro "22" State Type of Well: Oil Well Gas Well X Other 2. Name of Operator Well No. Louis Dreyfus Natural Gas Corp. 4 3. Address of Operator Pool name or Wildcat 14000 Quail Springs Parkway - Suite 600 - Oklahoma City, OK 73134 Scharb; Wolfcamp, SE 4. Well Location Unit letter 1650' feet from the North line and 1880' feet from the West line. Section Township **19S** Range 35E **NMPM** l ea County 10. Elevation (Show whether DR, RKB, RT, Gr, etc.) 3752 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB X COMPLETION OTHER: OTHER: Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propropsed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 8/03/01 Spud Well. 8/04/01 ran 13 3/8", 48#, H-40 csg, set at 597', cemented lead w/310 sks 35/65 Poz C, tailed w/180 sks Class C. Circulated 166 sks to reserve pit. Plug down @ 8:00 a.m. Wait on cement 27 hrs. commenced drilling. 8/16/01 ran 8 5/8", 32#, J-55 & MAV80 csg, set at 5,119', cemented lead w/1300 sks 35:65 poz Class C, tailed w/220 sks Class C. Cement did not circulate, spoke w/Buddy @ OCD in hobbs, received approval to top out w/1". With 1" cemented w/111 sks 35:65 Poz C, circ. 14 sks to reserve pit. WOC 23 hrs., commenced drlg. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Regulatory Technician 08/24/01 Carla Christian Type or print name 405-749-5263 Telephone No. (This space for State use) Paul Geologist BARE 2 8 2008 APPROVED BY TITLE

Conditions of approval, if any:

