(July 1992)			3407 · Inst.	ructions === side)	OMB NO PROVED
	DEPART 🚕	200 1 0 0 0 1 2 2	7369		Expires: February 28, 1995  5. LEASE DESIGNATION AND SERIAL NO.
	BURE DAG	59	470	tyr (s.) Milliografi	NM-54882
APP	LICATION FL	. 0 /	o los EN		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
la. TIPE OF WORK	(A)	10/		^	
b. Tipe of well	ORILL 🗓 🚊 🥷	30-025	-35714. 36	,9	7. UNIT AGREEMENT NAME
OIL XX	CAS OTHER		SINGLE MULT	IPLE	S
2. NAME OF OPERATOR	ULLE COTALE		ZONE X ZONE		S. FARMOR LEASE NAME WELL NO.
CONCHO 6 & GAS CORP. (JIM BLOUNT) 915-683-7443					WYNELL FEDERAL # 4  9. API WELLNO.
3. ADDRESS AND TELEPHONE NO.					
110 WEST LOU	10. FIELD AND POOL, OR WILDCAT				
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*)  800' FNL & 660' FEL SEC. 15 T19S-R33E LEA CO. NM					TONTO - SEVEN RIVERS
At proposed prod. zone SAME					11. SEC., T., E., M., OR BLE. AND SURVEY OR AREA
Unit D					SECTION 15 T19S-R33E
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE					12. COUNTY OF PARISH   13. STATE
Approximately 40 miles Southwest of Hobbs, New Mexico					LEA CO. NEW MEXICO
LOCATION TO NEARE	ST TIVE TO		O. OF ACRES IN LEASE	17. NO. OF	ACRES ASSIGNED
13. DISTANCE FROM PROPOSED LOCATIONS 320					40
TO NEAREST WELL. OR APPLIED FOR, ON T	DRILLING, COMPLETED		ROPOSED DEPTH	20. ROTAR ROTA	OR CABLE TOULS
21. ELEVATIONS (Show w	hether DF, RT, GR, etc.)	1		ROTA	22. APPROX. DATE WORK WILL START
		3683' GR.			When Approved
23. PROPOSED CASING AND CEMENTING PROGRAM					
SIZE OF ROLE GRADE SIZE OF CASING WEIGHT FER FOOT SETTING DEPTH					
25"	Conductor	NA cospec	40'	Cement	to surface with Redi-mix
11"	K-55 8 5/8"	32	1450 1487	800 Sx	to surface with Redi-mix
7 7/8"	K-55 4½"	11.6	3800'	1	Estimate top cem. 1200'
<ol> <li>Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix.</li> <li>Drill 11" hole to 1450'. Run and set 1450' of 8 5/8" K-55 32# ST&amp;C casing. Cement with 800 Sx. of Class "C" cement, 500 Sx. of Halco Light + additives, tail in with 300 Sx. of Class "C" cement + 2% CaCl, + ½# Flocele/Sx., circulate cement to surface.</li> <li>Drill 7 7/8" hole to 3800'. Run and set 3800' of 4½" 11.6# K-55 ST&amp;C casing. Cement with 250 Sx. of Class "C" Halco Light + additives, tail in with 200 Sx of Class "C" cement + 2% CaCl, + ½# Flocele/Sx. Estimate top of cement 1200' from surface.</li> </ol>					
·					
WITNESS 858" CASING CAT JOB					
APPROVAL SUBJECT TO					
Capitan Controllad Water Rocks  ABOVE SPACE DESCRIPE PROMOTED PROGRAM  SPECIAL STIPULATIONS					
A ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive table and proposal is to drill or repen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowds in which begins, if any.					
	Constitutions (Constitutions)	• • • • • • • • • • • • • • • • • • •	depths. Give blowdes and entered	of the language of the languag	
SIGNED .	et Jan	CO TITLE A	gent	···	05/16/01
(This space for Federal or State space use)					
PERMIT NOAPPROVAL DATE					
Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereof.					
CONDITIONS OF APPROVAL IF ANY:					
	101 10= -	ACTINO .			
APPROVED BY	/S/ JOE G. LAF	M FIEL	D MANAGER		SEP 9 7 7001
*See Instructions On Reverse Side APPROVATE FOR 1 YEAR					

ON TISMSON ON TOWN SON

IS JOE G. LARA