NT MEXICO OIL CONSERVATION COMMIS' W

SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST

Operat	or_	Texaco	T	10		Lease, //	b Fdhi	Unit "	MYS/ N	ell o. /
Locati		Unit /	Sec	_	Twp	20	Rge	<u>n NIA - 5</u> 7	County	/
of Wel				36	Type of		od of Prod	F .	Medium	Choke Size
Upper		Name of Re	1/1	111	(Oil or		Art Lift	(Tbg o	or Csg)	19/11
Compl Lower	-50	uth Salt	Loke	Atoka	Gas	F	low .	169	?	18/64
Compl	Sol	th Salt	Lake	Morrow	Gas	* Sh	ut-in	The		
					FLOW	TEST NO. 1		7		
Both 2	zone	es shut-in	at (ho	ur, date):_	10:00 A	m 12	2-12-7	7/		
				e):			2 - 13 - 7	7 / co	Upper ompletion	Lowe r Completion
									X	-
		•		_		ρ:	•		1240	710
						•			1/0	Yes
		-							12/10	
			•			p.4	41			7/0
						اکھر	•		30	7/0
Pressu	n.e	at conclus	ion of	test	• • • • • • • • •			•••••	540	710
Pressu	ше	change dur	ing te	st (Maximum	minus Min	imum)95.4	•		1210	
Was pi	ress	sure change	an in	crease or a	decrease?	• • • • • • • • • •	Total Ti		<u>lecre</u> ase	2
Well o	cl.os	sed at (hou	r, date	e): <u>/0:0</u>	An 12	2-14-71	Producti	_	this.	
Oil Pı D uri ng	rodu g Te	est:	, bbls	Grav.		s Production ring Test		e_MCF	GOR	5,000
Remarl	KSI 🕽	* Morr	א אמנו	Gas ha	5 N.J.	sales c	onnection			
					ET OW	TEST NO. 2				
				-) -				0.	Upper	Lower
	_		-						mpletion	_
						• • • • • • • • • •				
Pressi	ıre	at beginni	ng of	test	• • • • • • • • •	• • • • • • • • • • •	• • • • • • • • • •	•••••	·· <u>·</u>	
S ta bi]	Li.ze	ed? (Yes or	No)	• • • • • • • • • • •	• • • • • • • • •	• • • • • • • • • • •	• • • • • • • • •	••••-		
Maximu	nı p	ressure du	ring to	est	• • • • • • • • •	• • • • • • • • • •	•••••			
Minim	nn p	ressure du	ring to	est	• • • • • • • • • • • • • • • • • • • •		• • • • • • • • • •			
Pressi	nie	at conclus	ion of	test	• • • • • • • • •	• • • • • • • • • •	• • • • • • • • • •			***************************************
Pressu	ıre	change dur	ing te	st (Maximum	minus Min	imum)	• • • • • • • • •			
						• • • • • • • • • •				
							Total tim	e on		
Oil Pi	rodu	ection	hhla	· Crave	Gas	Production		MOE - C	±∩₽	
Dar.Tif	3 10	1 .		; Grav	;Dur.	ing lest	- /		on	
ne mar l	(Si	HNN	iua/	ZONE -	>6dveda	tion Te	5/			
	-	_	at the	informatio	n herein c	ont ai ned is	true and c	omplete	to the b	est of my
knowle	_		n 0 40	. ~		/Operat	or TEXA	tco I	رمدی (۱۵	
				71 ion Commiss		By		XIII		
	بمن. ا		1) /	A. Committees.			7	10100	~ //	
3 y _	_//	A STATE OF THE STA		DISTRICT	1 1	Title_	ASST	DIS	I.S	JUPT.
.itle_		<u>serady</u>	120H	DISMICI	. 1		12-21-			-

- of Flow Test No. 1, the well shall again be shutragraph 3 above. 5. Following completin, in accordance wi
- 1. A packer leakage test shall be commenced on . _ multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized and for a minimum of two hours thereafter, provided however, that they need not remain shut-in more than 24 hours.
- 4. For Flow Test No. 1, one zone of the dual completion shall be product the normal rate of production while the other zone remains shut-in. Stest shall be continued until the flowing wellhead pressure has become stabilized and for a minimum of two hours thereafter, provided however, that the flow test need not continue for more than 24 hours.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the previously shut-in zone is produced.
- 7. All pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked with a deadweight tester at least twice.once at the beginning and once at the end, of each flow test.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the appropriate District Office of the New Mexico Oil Conservation Commission on Southeast New Mexico Packer Leakage Test Form Revised 11-1-58, together with the original pressure recording gauge charts with all the deadweight pressures which were taken indicated thereon. In lieu of filing the aforesaid charts, the operator may construct a pressure versus time curve for each zone of each test, indicating thereon all pressure changes which may be reflected by the gauge charts as well as all deadweight pressure readings which were taken. If the pressure curve is submitted, the original chart must be permanently filed in the operator's office. Form C-116 shall also accompany the Packer Leakage Test Form when the test period coincides with a gas-oil ratio test period.

	\$** * 				
	♣		**************************************		
<u>+, i : </u>					
		l to i i i i l i t t l i i i i i i i i i i i i i i i i	+ : +		
	<u> </u>				
444					
					111
				Judillijii del	
					<u> </u>
					The second second
				RECE	
				OIL CONSU	5.4171
					#1217
					11 17 17 41
				on const	the the
				408)	poi '''