

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☐ other Water Injection Well

2. NAME OF OPERATOR
Anadarko Production Company

3. ADDRESS OF OPERATOR
P.O. Box 806 Eunice, New Mexico 88231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FSL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
WATER ACIDIZE	<input checked="" type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input checked="" type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)			

5. LEASE
LC 065447

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Teas Yates Unit

8. FARM OR LEASE NAME
Tract 3

9. WELL NO.
2

10. FIELD OR WILDCAT NAME
Teas Yates Seven Rivers

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 13, Twp 20S, Rg 33E

12. COUNTY OR PARISH
Lea

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3601' Est. GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. RUPU. TOH w/Injection Pkr & PVC lined tbg.
2. Set 8' Hydromite plug @ 3318'-3310'.
3. TIH w/cement retainer set above hole in csg @ 3300'-3310'. Cement squeeze hole w/100 sx Class "C" Cement. Circ out excess cement.
4. TOH w/tbg. TIH w/bit. CO to 3481'. TOH w/bit.
5. TIH w/Treating Pkr. Acidize w/6000 gal 20% NE-FE Acid in four stages. Flush w/100 bbls 2% KCL fluid. TOH w/tbg.
6. TIH w/PVC Lined Tbg & Injection Pkr. Resume water injection.

DEC 15 1982

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Original
SIGNED by Howard D. Zerk TITLE Production Foreman DATE December 14, 1982

APPROVED (This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JAN 21 1983

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side