For (F	m 9-	881 a (51)				
, 4	4	ď.	37 F4		10 T	
		C	ΕC	6	195/	D
\		الد	•	į А.	e do s 1 (اراز	ER.

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

and Office .	Las	Cruces
ease No	0654	147
Jnit	#J#	. RAB

SUNDRY NOTICES AND REPORTS ON WELLS

IOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
IOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	December 4 , 19_57
	December 4 , 17 21
	m. $\left\{\begin{array}{c} N \\ S \end{array}\right\}$ line and 1980 ft. from $\left\{\begin{array}{c} E \\ W \end{array}\right\}$ line of scc. 13 (Meridian)
T.e.	v of Subdivision) (State or Territory)
(Field) (County	y or subdivision)
f and conserved depths to objective sands: show s	AILS OF WORK sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
ud 16" hole 6 PM Oct. 31, 195	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- il other important proposed work)
ud 16" hole 6 FM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- liother important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtr
ud 16" hole 6 FM Oct. 31, 199 -3/8" csg. set at 86'. -3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-liother important proposed work) 57. at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtroaving from above. Stuck tools again d reverse circulator & washed over too.
ud 16" hole 6 FM Oct. 31, 195 -3/8" cag. set at 86'3/4" cag. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- li other important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtr caving from above. Stuck tools again d reverse circulator & washed over tool case. W/T.P. shoe & carried down w/bit
ud 16" hole 6 PM Oct. 31, 199 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- liother important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtr caving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'.
ud 16" hole 6 FM Oct. 31, 199 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 6 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld of om 875-1002' in red beds. No	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) 57. at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtroaving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. obtained from Mr. Protz, Potash C
ud 16" hole 6 PM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapseld om 875-1002' in red beds. Note approval to cmt. 8-5/8" America & Mr. Prost, USGS,	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- liother important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtr caving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. obtained from Mr. Protz, Potash C Artesia.
ud 16" hole 6 PM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapseld om 875-1002' in red beds. Note approval to cmt. 8-5/8" America & Mr. Prost, USGS,	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtroaving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. obtained from Mr. Protz, Potash Cartesia.
ud 16" hole 6 FM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld of ome 875-1002' in red beds. No one approval to cmt. 8-5/8" America & Mr. Prost, USGS, thed 10-3/4" csg. from 521'.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtreaving from above. Stuck tools again dreverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. obtained from Mr. Protz, Potash Cartesia. from 86' but it would not come. Left
ud 16" hole 6 FM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld of ome 875-1002' in red beds. No one approval to cmt. 8-5/8" America & Mr. Prost, USGS, thed 10-3/4" csg. from 521'.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- liother important proposed work) 57. at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtr caving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. obtained from Mr. Protz, Potash Cartesia.
ud 16" hole 6 FM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld of ome 875-1002' in red beds. No one approval to cmt. 8-5/8" America & Mr. Prost, USGS, thed 10-3/4" csg. from 521'.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtreaving from above. Stuck tools again dreverse circulator & washed over tools. csg. w/T.P. shoe & carried down w/bit o more water sand found below 755'. csg. obtained from Mr. Protz, Potash Cartesia. from 86' but it would not come. Left in writing by the Geological Survey before (AMER) may be commenced.
ud 16" hole 6 FM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld of ome 875-1002' in red beds. No one approval to cmt. 8-5/8" America & Mr. Prost, USGS, died 10-3/4" csg. from 521'. tempted to pull 13-3/8" csg. I understand that this plan of work must receive approval company SOSTMENN CALIFORNIA IN	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) 57. at 521' in 13" hole to stop caving entry. Mater sand 728-755' (240' wtr caving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. Gbtained from Mr. Protz, Potash Cartesia. from 86' but it would not come. Left in writing by the Goological Survey before particular be commenced.
ud 16" hole 6 FM Oct. 31, 199 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 6 665' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld on one approval to cmt. 8-5/8" America & Mr. Prost, USGS, diled 10-3/4" csg. from 521'. tempted to pull 13-3/8" csg. I understand that this plan of work must receive approval company SOUTHERN CALIFORNIA For	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) 57. at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtr caving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. Gbtained from Mr. Protz, Potash of Artesia. from 36' but it would not come. Left in writing by the Geological Survey before (ATTRILLEUM CORP.
ud 16" hole 6 FM Oct. 31, 195 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 8 865' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld of ome 875-1002' in red beds. No one approval to cmt. 8-5/8" America & Mr. Prost, USGS, died 10-3/4" csg. from 521'. tempted to pull 13-3/8" csg. I understand that this plan of work must receive approval company SOSTMENN CALIFORNIA IN	sizes, weights, and lengths of proposed casings; indicate mudding jobs, comentil other important proposed work) 57. at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtr caving from above. Stuck tools again d reverse circulator & washed over too cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. Gbtained from Mr. Protz, Potash of Artesia. from 86' but it would not come. Left in writing by the Geological Survey before (AMER) may be commenced.
ud 16" hole 6 FM Oct. 31, 199 -3/8" csg. set at 86'3/4" csg. mudded in red beds om 483'. Hole bailed dry-no hole). Stuck bit 6 665' by 875' & fished 7 days. Rigges recovered. n 8-5/8" - 32# S.H. lapweld on one approval to cmt. 8-5/8" America & Mr. Prost, USGS, diled 10-3/4" csg. from 521'. tempted to pull 13-3/8" csg. I understand that this plan of work must receive approval company SOUTHERN CALIFORNIA For	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) 57. s at 521' in 13" hole to stop caving entry. Water sand 728-755' (240' wtreaving from above. Stuck tools again dreverse circulator & washed over tools. cag. w/T.P. shoe & carried down w/bit o more water sand found below 755'. cag. obtained from Ar. Protz, Potash of Artesia. from 86' but it would not come. Left in writing by the Geological Survey before (AMER.) may be commenced.

80' af 13-3/8" cag, in hole from 6-86'.
Cartd, 8-5/8" # 1001' in red beds w/510 cu, ft, of lil Fre-mix regular cast, a blandx w/4% gel (190% of theoretical). Had good circulated approx, 100 sax cat, to pit, Cart, witnessed by D. E. Frotz, Potash Co. of America. 10/28/57 sail-tested 8-5/8" cag, l hr. - no entry.
11/28/57 sail-tested 8-5/8" cag, l hr. - no entry.
3/0. Fing & 60' cat; to l' below 8-5/8" shoe & bail-tested l hr. -

ne emery. Prilling 8" hole shead.