

TOOLS USED

Rotary tools were used from 0 feet to 1470 feet, and from feet to feet
 Cable tools were used from feet to feet, and from feet to feet

DATES

January 24, 1960 ~~February 24~~ P&A January 24, 1960

The production for the first 24 hours was barrels of fluid of which % was oil; %
 emulsion, % water, and % sediment. Gravity, °Bé.
 McGraw-Hill; cost per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
 Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller
 Driller Driller

FORMATION RECORD

FROM-	TO-	TOTAL FEET	FORMATION
0	57	57	Surface Sand & Caliche
57	1470	1413	Red Beds
1470	2980	1510	Anhydrite & Salt
2980	3032	52	Anhydrite
3032	3148	116	Dolomite
3148	3412	264	Sand & Dolomite
3412	3470	58	Dolomite

LOG TOPS:

Base of Salt 2980' (+674')
 Winkler Dolomite 3032' (+622')
 Yates 3148' (+506')
 Seven Rivers 3412' (+242')

Spotted cement plugs at: 3350' - 3470' 55 sk.
 2900' - 3000' 35 sk.
 1800' - 1950' 52 sk.
 550' - 700' 5 sk.
 260' - 360' 40 sk.
 Top of 8 5/8" casing 5 sk.

Erected prescribed Marker in 8 5/8" casing.

(OVER)

17-43084-4