(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

				New Mexico					
			M	MM-0800-1					
•	Unit	P	epite	: 54	1				
	50	3!	!	1		ì	4.5	1	, - -

SUNDRY NOTICES AND REPORTS ON WELL'S

NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	ļ	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

	February 15.					
Weil No. is located	660 ft. f	$rom_{-} \left\{ \begin{matrix} N \\ \bullet \end{matrix} \right\}$ line ar	and 1980 ft. from $\left\{ egin{array}{c} \egin{array}{c} egin{array}{c} egin{array}{c} egin{array}{c} \egin{array}{c} egin{array}{c} \egin{array}{c} a$	e of sec. 35		
NE/4 NM/4 Sec. 35	20-4	33-F	MIN			
(1/4 Sec. an 1 Sec. No.)	(Twp.)	(Range)	(Meridian)			
Wildcat	Lea		New Mexico			
(Field)	(Co	unty or Subdivision)	(State or Territ	ory)		

The elevation of the derrick floor above sea level is 3670 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill the Shell-Federal Well No. 1 as a 3500° Tates-Seven Rivers test with Rotary Tools as follows: Drill 11" hole to 300° and coment 8 5/8" 32# casing w/ 300 sacks. Circulate cement. Drill 7 7/8" hole to 3500° and cement 4 1/2" 9.5# casing w/350 sacks.

(If above is unsatisfactory, we will follow cementing and casing program as required by the U. S. G. S.)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.						
Company	#1 Cinco Production Company,	Ltd.				
Address	P. O. Reat 1026					
	Midland, Texas	Ву				
		Title Office Manager				