

(SUBMIT IN TRIPLICATE)

U. S. Land Office Las Cruces

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Lease or permit No. 029513

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, March 19, 19 45

D. D. Swearingin

Well No. 2 is located 1980 ft. from N line and 1980 ft. from E line of sec. 9

SW 1/4 Sec. 9  
(1/4 Sec. and Sec. No.)

20-8  
(Twp.)

34-E  
(Range)

N.M.P.M.  
(Meridian)

North Lynch  
(Field)

Lea  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 3635 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was drilled to total depth of 4769' without encountering oil or gas production, and has been abandoned, plugging in the following manner. Hole was filled with heavy mud and the 7" casing, mudded at 4426', was all pulled. Cement plugs were spotted as follows: 30 sacks, 3850'-3750'; 30 sacks, 3230'-3130' (at base of salt); and 30 sacks, 1625'-1525' (at top of salt and in bottom of 8-5/8" casing). Pulled 974' of 8-5/8" casing and spotted a plug of 20 sacks of cement at 1005' to 950' (in the top of the parted 8-5/8" casing). A cement plug of 30 sacks was spotted from 315' to 280', in the bottom of the 13-3/8" casing; and the required 4" pipe marker cemented in the top of the hole with 20 sacks, leaving all 13-3/8" casing cemented in the hole. Above work was completed 12-15-44 and the location is now cleaned up and ready for inspection.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE TEXAS COMPANY

Address Box 1270

Midland, Texas

By [Signature]

Title Drig. & Prod. Foreman