Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. NM-06531-A
6. If Indian, Allottee or Tribe Name

## **SUNDRY NOTICES AND REPORTS ON WELLS**

SUBMIT IN TRIPLICATE		
Type of Well Gas Gas		
☐ Gas Well ☐ Other ☐ Other		8. Well Name and No.
Name of Operator		Lea Unit No. 4
Marathon Oil Company		9. API Well No.
Address and Telephone No.		30-025-02424
P. O. Box 552, Midland, TX		10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey Description)		Lea (Bone Spring)
Unit Letter H. 1980' FNL &	660' FEL	11. County or Parish, State
Section 11, T-20-S, R-34-E		Lea County, NM
CHECK APPROPRIATE B	OX(s) TO INDICATE NATURE OF NOTI	CE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE	OF ACTION
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
•	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
Describe Proposed or Completed Operations (Clearly give subsurface locations and measured and true on 10-9-91 Marathon Oil Co.	other	ecomplete the above referenced
Describe Proposed or Completed Operations (Clearly give subsurface locations and measured and true on 10-9-91 Marathon Oil Cowell to the Bone Spring for the Safety anchors were teamed to the lockout-tage w/flanged gate valves.	state all pertinent details, and give pertinent dates, including estimative rical depths for all markers and zones pertinent to this work impany initiated operations to remation. Following is the processed 9-9-91. RU Pool Well Servicut procedure). Removed wellhead Installed 6" 1500 series hydra	complete the above referenced dure:  ce. Disconnected power to d. Installed 6" spacer spool ulic BOP. RU Cable Services.
Describe Proposed or Completed Operations (Clearly give subsurface locations and measured and true  On 10-9-91 Marathon Oil Cowell to the Bone Spring fo  1. Safety anchors were tewell (used lockout-tage w/flanged gate valves. Unloaded & racked 2 7/	state all pertinent details, and give pertinent dates, including estimal vertical depths for all markers and zones pertinent to this work impany initiated operations to remation. Following is the processted 9-9-91. RU Pool Well Servicut procedure). Removed wellhead	ce. Disconnected power to d. Installed 6" spacer spool ulic BOP. RU Cable Services. down w/Reda pump on 3 1/2"
Describe Proposed or Completed Operations (Clearly give subsurface locations and measured and true)  On 10-9-91 Marathon Oil Cowell to the Bone Spring four subsurface locations were termed to the Bone Spring four subsurface and true well (used lockout-tage w/flanged gate valves. Unloaded & racked 2 7/tbg (hauled Reda pump blind rams. SDFN.  2. RU Computalog. WIH w/Cleared w/Shanon Shaw, below 13,820'. Set plutop of plug (2 runs). & dumped 35' cmt on plus	state all pertinent details, and give pertinent dates, including estimative tical depths for all markers and zones pertinent to this work impany initiated operations to remation. Following is the procested 9-9-91. RU Pool Well Servicut procedure). Removed wellhead Installed 6" 1500 series hydra 8" N80 workstring. POOH laying	complete the above referenced dure:  ce. Disconnected power to d. Installed 6" spacer spool ulic BOP. RU Cable Services. down w/Reda pump on 3 1/2" e rams to 2 7/8". Closed  basket. Tagged btm @ 13,881'. IH w/7" CIBP. Could not get bailer. Dumped 35' cmt on 00'. POOH. RIH w/dump bailer t plug @ 10,300'. POOH. RIH
Describe Proposed or Completed Operations (Clearly give subsurface locations and measured and true)  On 10-9-91 Marathon Oil Cowell to the Bone Spring four subsurface locations were termined to the Bone Spring four subsurface well (used lockout-tage w/flanged gate valves. Unloaded & racked 2 7/tbg (hauled Reda pump blind rams. SDFN.  2. RU Computalog. WIH w/Cleared w/Shanon Shaw, below 13,820'. Set plutop of plug (2 runs). & dumped 35' cmt on pluw/dump bailer & dumped (See Attachment 1)	mpany initiated operations to remation. Following is the process that all process per states and some per states are process. The process of	complete the above referenced dure:  ce. Disconnected power to d. Installed 6" spacer spool ulic BOP. RU Cable Services. down w/Reda pump on 3 1/2" e rams to 2 7/8". Closed  basket. Tagged btm @ 13,881'. IH w/7" CIBP. Could not get bailer. Dumped 35' cmt on 00'. POOH. RIH w/dump bailer t plug @ 10,300'. POOH. RIH computalog. Closed blind rams.
Describe Proposed or Completed Operations (Clearly give subsurface locations and measured and true)  On 10-9-91 Marathon Oil Cowell to the Bone Spring four subsurface locations were termined to the Bone Spring four subsurface well (used lockout-tage w/flanged gate valves. Unloaded & racked 2 7/tbg (hauled Reda pump blind rams. SDFN.  2. RU Computalog. WIH w/Cleared w/Shanon Shaw, below 13,820'. Set plutop of plug (2 runs). & dumped 35' cmt on pluw/dump bailer & dumped (See Attachment 1)	mpany initiated operations to remation. Following is the processed 9-9-91. RU Pool Well Servicut procedure). Removed wellhead Installed 6" 1500 series hydra 8" N80 workstring. POOH laying to ESP in Midland). Changed pip 5 7/8" gauge ring & 3 1/2" junk BIM, to set CIBP @ ±13,860'. War and gauge 12,8 and ga	complete the above referenced dure:  ce. Disconnected power to d. Installed 6" spacer spool ulic BOP. RU Cable Services. down w/Reda pump on 3 1/2" e rams to 2 7/8". Closed  basket. Tagged btm @ 13,881'. IH w/7" CIBP. Could not get bailer. Dumped 35' cmt on 00'. POOH. RIH w/dump bailer t plug @ 10,300'. POOH. RIH computalog. Closed blind rams.