Indian Agency	(SUBMIT IN TRIPLICATE)	U.S. Land Offices Cruces
	•	Lease or permit NO29518
	UNITED STATES	·
	PARTMENT OF THE INTER	RIOR
Leese No	GEOLOGICAL SURVEY	
SUNDRY NO	TICES AND REPORT	S ON WELLS
	<u> </u>	
NOTICE OF INTENTION TO DRILL		OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT		OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPA		OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZI		OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER C.	ASING SUPPLEMENTARY WEL	L HISTORY
NOTICE OF INTENTION TO ABANDON WELL		
	BY CHECK MARK NATURE OF REPORT, NOTICE	, OR OTHER DATA)
	Wink, To	X38. August 4. 197
S.Lea		
Well No. 2 is located 1	980 ft. from $\begin{bmatrix} N \\ n \end{bmatrix}$ line and 660	ft from (E) line of sec15
	X(S)	
Et of NE toof Sec. 15	205 34 E	N.M.P.M.
and the second	(Twp.) (Range)	(Meridian)
		Mexico
(Field)	(County or Subdivision)	(State or Territory)
The elevation of the derrick floor :	above sea level 3635 ft	
	DETAILS OF WORK	
State names of and expected depths to objective	re sands; show sizes, weights, and lengths of pr ; points, and all other important proposed we	roposed casings; indicate mudding jobs, cement-
***	pointe, and an other important proposed we	SFR)
ollows:	lan of abandoning the	above well is as
OTTOMS!		لي ين المنظلم (
	illed with mud to hot:	
Hole will be f		Om OT / 40 3038.
Hole will be fi	in the bottom of the	77 ABRINDING TO THE THE
ement plug will be set	in the bottom of the	7" casing
ement plug will be set Will part 7" of	in the bottom of the asing at approximately	V 2500' and after "
ement plug will be set Will part 7" of ulling 7" casing, hole	in the bottom of the asing at approximately will be mudded to 166	y 2500' and alter ' ' C
will be set Will part 7" of ulling 7" casing, hole et in the bottom of the nd pulled from approxim	in the bottom of the asing at approximately will be mudded to 160 a 9-5/8" casing. The mately 1325'.	y 2500' and after a b b 55' and coment plug 9-5/6" will be parted
will be set Will part 7" of ulling 7" casing, hole et in the bottom of the nd pulled from approxim Balance of the	in the bottom of the asing at approximately will be mudded to 166 9-5/8" casing. The mately 1325'. hole will be mudded t	y 2500' and after to 5 55' and coment plug 9-5/8" will be parted
will be set Will part 7" of ulling 7" casing, hole et in the bottom of the ad pulled from approxim Balance of the ustomary 4" pipe marked	in the bottom of the asing at approximately will be mudded to 160 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come	y 2500' and after the 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas
will be set Will part 7" of ulling 7" casing, hole et in the bottom of the nd pulled from approxim Balance of the	in the bottom of the asing at approximately will be mudded to 160 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come	y 2500' and after a b 5 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas
ement plug will be set Will part 7" of ulling 7" casing, hole et in the bottom of the nd pulled from approxim Balance of the ustomary 4" pipe market lunderstand that this plan of work must re-	in the bottom of the asing at approximately will be mudded to 160 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come ceive approval in writing by the Geological Su	y 2500' and after a b 5 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas
will part 7" of Will part 7" of ulling 7" casing, hole et in the bottom of the Balance of the ustomary 4" pipe marked Junderstand that this plan of work must re Company	in the bottom of the asing at approximately will be mudded to 166 a 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come ceive approval in writing by the Geological Su Company	y 2500' and after the 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas
ement plug will be set Will part 7" of ulling 7" casing, hole et in the bottom of the nd pulled from approxim Balance of the ustomary 4" pipe market lunderstand that this plan of work must re-	in the bottom of the asing at approximately will be mudded to 166 a 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come ceive approval in writing by the Geological Su Company	y 2500' and after a b 5 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas
will part 7" of Will part 7" of ulling 7" casing, hole et in the bottom of the Balance of the ustomary 4" pipe marked Junderstand that this plan of work must re Company	in the bottom of the asing at approximately will be mudded to 166 a 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come ceive approval in writing by the Geological Su Company	y 2500' and after a b 5 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas
will part 7" of Will part 7" of ulling 7" casing, hole et in the bottom of the Balance of the ustomary 4" pipe marked Junderstand that this plan of work must re Company	in the bottom of the asing at approximately will be mudded to 166 a 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come ceive approval in writing by the Geological Su Company	y 2500' and after a b 5 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas
will part 7" of Will part 7" of ulling 7" casing, hole et in the bottom of the Balance of the ustomary 4" pipe marked Junderstand that this plan of work must re Company	in the bottom of the asing at approximately will be mudded to 160 a 9-5/8" casing. The nately 1325'. hole will be mudded to r will be set and come ceive approval in writing by the Geological Su Company K. Texas. By	y 2500' and after a b 5 55' and cement plug 9-5/6" will be parted to the surface and the ented in 13" surface cas