



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **LC-066126-C**
Unit **Cruces No. 5**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	☒
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 16, 1959

CRUCES

Well No. **5** is located **330** ft. from **[S]** line and **992** ft. from **[E]** line of sec. **26**
SE/4 SE/4 Sec. 26 **T-20-S** **R-34-E**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Lynch **Lee County** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3733** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Cemented 4-1/2" casing at 3799' (11.64') with 228 sacks regular 40% DD (930 cu. ft. 172 sz. DD) followed by 100 sacks regular. Plug to 3749'. Ran temperature survey, top of cement at 741'. WOE 20 hours. Tested casing with 1800' for 30 minutes, no pressure loss.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Phillips Petroleum Company**

Address **Box 2105, Hobbs, New Mexico**

By *[Signature]*

Title **District Chief Clerk**