

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Carper Drilling Company, Inc. & T.J. Sivley  
(Company or Operator)

Threlkeld, Etal Fee  
(Lease)

Well No. 1, in NE 1/4 of NE 1/4, of Sec. 28, T. 20S, R. 34E, NMPM.

Undesignated Pool, Lea County.

Well is 500 feet from North line and 825 feet from East line

of Section 28. If State Land the Oil and Gas Lease No. is Fee Land

Drilling Commenced 10/17, 19. 62. Drilling was Completed 10/25, 19. 62

Name of Drilling Contractor Carper Drilling Company, Inc.,

Address 200 Carper Building, Artesia, New Mexico

Elevation above sea level at Top of Tubing Head 3693 DF The information given is to be kept confidential until, 19.

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7" OD	20 Lbs	New J-55	1641'	Float & Guide			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
8-3/4"	7" Od	1641	50 Sks Neat 175 Sacks of 50/50 Poz-Mix with 8% Gel 2% Cal. Chl. Cement Circulated	B-J Service		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Plugged as per hole

Result of Production Stimulation

Depth Cleaned Out

# RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

Rotary tools were used from 0 feet to 3775 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

## PRODUCTION

Put to Producing: Plugged as Dry Hole 10/26, 1962

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. 1583 - Rustler	T. Devonian	T. Ojo Alamo	
T. Salt 1710	T. Silurian	T. Kirtland-Fruitland	
B. Salt 3315	T. Montoya	T. Farmington	
T. Yates 3530	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash.	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta	T.	T. Morrison	
T. Drinkard	T.	T. Penn.	
T. Tubbs	T.	T.	
T. Abo	T.	T.	
T. Penn.	T.	T.	
T. Miss.	T.	T.	

## FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	700	700	Red Beds				
700	1500	800	Red Rock and Shales				
1500	1710	210	Anhydrite				
1710	3315	1650	Salt and Anhy.				
3315	3543	228	Anhydrite and dolomite				
3543	3584	41	Shaley Sands				
3584	3614	30	Dolomite				
3614	3645	31	Sands and shales				
3645	3705	60	Anhydrite and Dolomite				
3705	3775	70	Anhydrite and dolomites				

This well plugged as dry hole on 10/25 and 10/26/62 in the following manner:

130 Sack 50/50 Neat Poz-Mix Cement Plug with 0 Gel. set from 3775 back to 3200' (Base of Salt 3315') 175 Sacks of 50/50 PozMix Cement with 10% Gel plug set accross salt section from 3200' back to 1550 in 7" OD Casing set at 1641'. Saturated Salt Mixture. Top of Salt 1710. No Casing Recovered as it was cemented back to ground surface. Salt Gel Mud from 1550 back to surface and displaced with 30 sack neat Cement Plug from 7" OD Casing down 150 Ft. from Surface. Regulation marker erected.

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Carper Drilling Company, Inc.,  
Company or Operator: T.J. Sivley  
Name: T.J. Sivley  
Address: P.O. Box 66, Artesia, New Mexico  
Date: 10/31/62  
Title: Operator