

Budget Bureau No. \_\_\_\_\_  
Approval Exp. \_\_\_\_\_

Land Office No. \_\_\_\_\_  
Locality No. \_\_\_\_\_  
U.S.A. \_\_\_\_\_

**APPROVED**  
JAN 12 1959

(SUMMIT IN TRIPLED)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECD

JAN 19 1959

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

T. E. GODFREY  
ACTING DISTRICT SURGEON

**SONDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 6, 1959

1959

Mr. Sivley - Foothills Silver

Well No. 1 is located 1980 ft. from [S] line and 1980 ft. from [E] line of sec. 28.

NWSE = 26 20-8 34-B NMM

(Sec. and Sec. No.) (Crs.) (Range) (Section)  
Lynch Pool Extension Lot New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3713 ft.

**DETAILS OF WORK**

(State names of and reported depths to objective casing show diam., weights, and lengths of proposed casings; indicate mudding jobs, concreting points, and all other important production work)

On December 21, 1958 - 3583' - 5-1/2" OD 14# J-55 New Seamless Casing was landed at 3585' and cemented with 575 sacks of 1:1 Pom-tix Cement with 6% Gel and 1/2 Calcium Chloride and 125 sacks of neat cement with 1% Calcium Chloride on bottom. The fluid used to mix cement was brine water secured from PCA mine saturated with salts common to the zones penetrated. Approximately 100 sacks of cement was circulated back to ground surface. Drilled down 2:00 P.M.

On January 1, 1959 hole was bailed dry and plug drilled on cement and casing set. After plug drilled, hole tested for one hour and found to be satisfactory. Drilling ahead resumed. Drilling at 3713 at 8:00 A.M. January 6, 1959.

Base of dial: 3280' - Casing set 305' below this point.

I understand that this plan of operations must be submitted to the Geological Survey before operations may be commenced.

Company: T.J. Sivley

Address: Box 1298

Artesia, New Mexico

By: *T.J. Sivley*  
Title Operator

10290