

Form 9-331a
(Feb. 1957)

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe, N.M.
Lease No. DM-039856
Unit (0)

APPROVED

APR 29 1959

A. P. KLEMAN
DISTRICT ENGINEER

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

MAR 16 1959

U. S. GEOLOGICAL SURVEY
BOBBS, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 13, 1959

T.J. Sivley - Federal Silver

Well No. 4 is located 640 ft. from N line and 1600 ft. from E line of sec. 36

SEGE - 34

2CU

34R

NUMA

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Lynch Pool Ext.

Lee

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Proposal is made to drill this well to an approximate depth of 3720'. The drilling of this well will conform to rules of Federal Order E-111-1. 1600' - 2-3/4" O.D. Grade 5 Casing will be set in basal hostler anhydrite at top of salt section or as determined necessary by regulator representative and cemented with not less than 150% of the calculated volume necessary to circulate cement to ground surface. 3720' - 2-1/2" O.D. 4-30 seamless casing will be set as salt protection string whilst is approx. 400' below base of salt and above expected Lynch pay zone in Silver No. 1 encountered at 3720'. Recommended minimal volume of cement will be used for testing purposes only. If the well is completed as a productive well, this string shall be re-cemented with sufficient cement to circulate the cement back to ground surface, and used as the Production String. Combination Tools will be used.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company T.J. Sivley

Address Box 1206

Artesia, New Mexico

By

Title

Operator

APPROVED

SEP 20 1954

U.S. DEPT. OF AGRICULTURE

WASHINGTON, D.C.