

APPROVED

*SUBJECT TO BELOW

JUN 21 1961

Form 9-881a
(Feb. 1961)

HOBBS OFFICE
E. W. STANDLEY
DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES

1961 JUN 27

AM 8:09

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

U.S. G.S. Form No. 42-R364-1
April, 1957 Edition (12-31-60)

Land Office, Santa Fe, N. M.

N. M. 01130

R

MAY 31 1961

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELL

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHEET
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHEETING OR REVISION
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING PLANING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REPAIRING OR REPAIR
NOTICE OF INTENTION TO ABANDON OR ABANDON		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ACCE Casing		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

INDICATE ABOVE BY CHECK MARK, NATURE OF TEST, TYPE OF OTHER TEST

42-42

19 61

Well No. 1 is located 330 ft. from line and 115 ft. from line of sec. 29

C. NW 1/4 NW 1/4 of 29, 20 South, 34 East
(Twp) (Range) (Section)

Undesignated Lea
(Field) (County or subdivision)

New Mexico
(State)

The elevation of the derrick floor above sea level is 3679 ft.

DETAILS OF WORK

(State names of soil expected together to claystone sand; show sizes, weights, and lengths of pieces of gravel, cobbles, and all other important material)

This test is located within a designated potato field.
Drilling and completion operations will be conducted in such a manner to conform with the regulations and practices as set out in R-111-A.

Proposed Total Depth=4000 feet

Surface Hole Size: 11" to 1650' Top of Salt; Surface Csg. 9 1/8" @ 1650' with 750 Sacks Cement

Intermediate Hole Size: 8" to 3125 (Base of Salt); Intermediate Csg. 7" @ 3125' with 50 Sacks Cement

Final Hole Size: 6" to T. D. approx. 4000' Oil String Csg. 4 1/2" @ 4000' with 1000 sacks Cement

The weights of the csg. will be 9 5/8: 32 lbs., 7 1/2: 27 lbs., and 4 1/2: 9 1/2 lbs. per ft. It is proposed to pull the intermediate csg. before final completion.

I understand that this plan of work must be approved in writing by the Geological Survey before operations may be commenced.

Company Earl G. Colton

Address 1546 Milan Building, San Antonio, Texas

By

Title Agent

* A USGS Engineer must be called in time to witness all cementing operations