

APPROVED
Subject below

COPY TO C. C.

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Form 9-331a
(Feb. 1961)

JUN 1 1961

HOBBS

(SUBMIT IN TRIPLICATE)

Land Office New Mexico

Lease No. 01130-5

Unit _____

E. W. STANDLEY
DISTRICT ENGINEER

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

RECEIVED

MAY 17 1961

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 16, 1961

Texaco-Federal

Well No. 1 is located 760 ft. from N line and 660 ft. from E line of sec. 30

NE 1/4 30 20-S 34-E NMPH
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3600 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a Seven Rivers Wildcat to an expected total depth of 3700'. A 12 1/4" hole will be drilled to the top of Anhydrite at approximately 1400' -- run 9 5/8" H-40, 32.30# casing cemented to surface. W.O.C. 24 hrs. & drill 8 3/4" hole to top of Seven Rivers, run 7" - J-55 20# casing and cement with sufficient volume to place. Cement to bottom of salt, drill into pay and if productive, pull 7" casing and run 4 1/2 - J-55 9.5" casing and circulate to surface. All operations will be in compliance with R-111-A. A U.S.G.S. engineer must be contacted in sufficient time to witness all cementing operations at the well site.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Gackle Drilling Company, Inc.

Address P.O. Box 2076

Hobbs, New Mexico

By R. F. Montgomery

Title Agent