


*SUBJECT TO BELOW

Form 9-581a
(Feb. 1961)



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R388.4
Approval expires 12-31-60.

New Mexico

Land Office

NEW 05218-4

Lease No.

4399

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 30

1961

Well No. 1 Fed. is located 330 ft. from [N] line and 2310 ft. from [E] line of sec. 33

Section 33
(1/4 Sec. and Sec. No.)

30 South 34 East
(Twp.) (Range)

N.M.P.M.
(Meridian)

Undesignated
(Field)

Log
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Rotary test well for oil and gas to be drilled to Seven Rivers Sand of Upper Permian, expected to be encountered at approximately 3000 feet; set approximately 1000 feet 8-1/2" O.D. surface string, cement to ground surface; set approximately 3000 feet 4-1/2" casing, salt protection string, cemented in the manner prescribed in H-111-A, U.S.G.S., depending on whether well is testing for production or whether production is obtained; will attempt to complete well from open hole below 3000 feet. Any changes in the foregoing will be made after and with the approval of the Supervising Engineer, U.S.G.S. All operations will be conducted in the manner prescribed by H-111-A. Plot of proposed well location attached.

* All casing and cementing tests must be witnessed by a U.S.G.S. Engineer. This office is to be contacted in sufficient time to make the necessary arrangements in case such tests will occur after normal working hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company G. L. MORSEWORTH, JR.

Address Republic National Bank Building
Dallas, Texas

G. L. MORSEWORTH, JR.

By

[Signature]

Title

Supervisor