

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office ~~Alamogordo~~, N. Mex.

Lease No. 08823

Unit

RECEIVED
JUL 31 1952

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 30, 1952

Well No. 1 is located 330 ft. from ^{xx}N line and ¹⁶⁵⁰~~136~~ ft. from ^{xx}E line of sec. 35

SE/4, SW/4 Sec. 35 20-S 34-W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Lynch Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3820 ft. est.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Depth of Yates sand is about 3720 to 3750', this location.

125' to 150' of 13-3/8" casing, cement circulated to top. Will use 10" casing landed about 1000'. 1400' of 8-5/8" landed. Oil string 3000' or 3700' of 5-1/2" - 14# casing to be cemented with 400 sacks cement, circulated by Halliburton Oil Well Cementing Company.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. H. Elder

Address Box 950

Midland, Texas

By *J. H. Elder*

Title Owner