

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office N. Mex.  
Lease No. 02127-A  
Unit C

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 30, 1952

Well No. 4 is located 990 ft. from N line and 1650 ft. from E line of sec. 35  
NE of NW 1/4 Sec. 35 20-S 34-E N.M. P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Lynch Lea New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3785 ft. est.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Depth of Yates sand is about 3725 to 3750' this location.  
 125' to 150' of 13-3/8" 68# Casing, cement circulated to top. Will use 10"  
 Casing landed about 1000'. 1400' of 8-5/8" landed. Oil sitting 3600' or 3700'  
 of 5-1/2" 14# Casing to be cemented with 500 sacks cement, circulated by  
 Halliburton Oil Well Cementing Company.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. H. Elder

Address Box 950

Midland, Texas

By 

Title Owner