

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
Other Agency
TE

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-064194

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal Hedges

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Lynch (Y-SR)

11. SEC., T., E., M., OR BLK. AND
SURVEY OR AREA

Sec. 35-20S-34E

12. COUNTY OR PARISH 13. STATE

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

William A. & Edward R. Hudson

3. ADDRESS OF OPERATOR

P.O. Box 9, Maljamar, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit E
2310' from north and 990' from west
lines of Sec. 35-20S-34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well was plugged and abandoned as follows:

August 22, 1989, set a "cast iron" bridge plug at 3650', spotted 75' (15 sks.) cement on top of plug, filled hole w/salt gel mud, spotted salt cement plug from 3375' to 1600' (200 sks.), spotted 75' (15 sks.) cement at the surface, installed a 4" x 8' marker with well data.

August 23, 1989, the location was cleaned of all debris.
August 29, 1989, the pits were filled in and the location was ripped 14" deep. The area was reseeded with 4# alkali sacaton and 20# four wing salt brush. The area is ready for final inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED Quinn Hudson TITLE Prod. Supt.

DATE 8/29/89

(This space for Federal or State office use)

APPROVED BY Adam Salameh TITLE Prod. Supt.

DATE 8-27-89

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

SEP 29 1989

OCD
HOBBS OFFICE