

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

U.S. CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

3a. Indicate Type of Lease
State ☒ Fee ☐
3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL, <input type="checkbox"/> GAS WELL, <input type="checkbox"/> OTHER- Injector	7. Unit Agreement Name West Pearl Queen Unit
2. Name of Operator Chevron U.S.A. Inc.	8. Farm or Lease Name
3. Address of Operator P.O. Box 670 Hobbs, NM 88240	9. Well No. 150
4. Location of Well UNIT LETTER F 1980 North 1980 FEET FROM THE LINE AND FEET FROM West 32 19S 35E THE LINE, SECTION TOWNSHIP RANGE NMPM.	10. Field and Pool, or Wildcat Pearl Queen
15. Elevation (Show whether DF, RT, GR, etc.) 3719' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Set CIBP @ 4725'. Found casing leak from 800' - 860'. 2-11-1986. Will P&A as follows:

- 1) Dump 35' of cement on top of CIBP @ 4725.
- 2) Establish circulation through 4 1/2" X 8 5/8" annulus. Cement down 4 1/2" casing with 300 sacks class "C" cement or until cement is circulated. Close 4 1/2" X 8 5/8" annulus and squeeze casing holes from 800' - 860' with 50 sacks of cement.
- 3) Install dry hole marker.
- 4) Clean and clear location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED P.H. Bailey Jr. TITLE Division Drilling Manager DATE 4-9-1986
ORIGINAL SIGNED BY JERRY SEXTON
APPROVED BY DISTRICT I SUPERVISOR TITLE _____ DATE APR 10 1986
CONDITIONS OF APPROVAL, IF ANY: