

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PERORATION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/1/62)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE O. C. C.
MAR 9 9 03 AM '64

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	Convert To Dual Injection Well

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico
(Place)

March 4, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company East Pearl-Queen Unit Well No. 35240 in B
(Company or Operator) (Unit)
NW 1/4 NE 1/4 of Sec. 34, T. 19 S, R. 35 E, NMPM, Pearl-Queen Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull rods, pump and tubing.
2. Perforate Zone IIB at 4908-4910' with four JSPF;
IIIA at 4924-4928' and 4940-4942' with two JSPF;
IIIB at 4951-4953' with four JSPF
3. Run tubing with packer and set packer @ 4800' between Zones I and IIA perforations and test for communication between Zone I and lower perforations.
4. Set packer at 4890' and treat with 500 gallons 15% Fe NEA.
5. Set permanent packer at 4800'.
6. Run 1 1/2" plastic coated tubing with dual packer spaced to set at 4740' with 2" plastic coated tubing under packer with seal assembly. Set packer.
7. Run 1 1/2" plastic coated tubing with seal assembly.
8. Hook up plastic coated well head and start injecting.

NMOCC Order No. R-2538

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Shell Oil Company

Company or Operator Original Signed By
By R. A. Lowery R. A. LOWERY

Position District Exploitation Engineer
Send Communications regarding well to:

Name Shell Oil Company
Address Box 1858 Roswell, New Mexico