DI	TRIBUTION	
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
TRANSPORTER	OIL	
	GAS	i i
PROMATION OFFIC	E	
OPERATOR		

WEW MEXICO OIL CONSERVATION COMMISSION HOBBS OFFICE A

Santa Fc, New Mexico

MISCELLANEOUS NOTICES

		····· C. C.	
MAR	9	9 ₀₃	AM '64

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention		Notice of Intention to	NOTICE OF INTENTION
to Change Plans		Temporarily Abandon Well	TO DRILL DEEPER
NOTICE OF INTENTION		Notice of Intention	Notice of Intention
TO PLUG WELL		to Plug Back	to Set Liner
Notice of Intention		Notice of Intention	Notice of Intention
to Squeeze		to Acidize	to Shoot (Nitro)
Notice of Intention	x	Notice of Intention	Notice of Intention Convert To Dual
to Gun Perforate		(Other)	(Other) Injection Well

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Roswell, New Mexico. March 4. 1964

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company	East Pearl-Queen Unit	Well No. 46 in	H
(Company or Operator)	Lease		(Unit)
SE 1/4 NE 1/4 of Sec	, т. 19 S , к. 35 E , ММРМ.,	Pearl-Queen	Pool
(40-acre Subdivision)			

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

- 1. Pull rods, pump and tubing.
- 2. Perforate Zone IIA at 4870-4871'and 4879-4882' with two JSPF and

at 4887" and 4894" with two JS each;

IIIA at 4914-4916' and 4924-4926' with two JSPF.

- 3. Run tubing with packer and set packer @ 4800' between Zones I and IIA and test for communication.
- 4. Set permanent packer at 4800'.
- 5. Run 11/2" plastic coated tubing with dual packer spa ed to set at 4710'
- with 2" plastic coated tubing under packer with seal assembly. Set packer.
- 6. Run 11/2" plastic coated tubing with seal assembly.
- 7. Hook up plastic coated well head and start injecting.

NMOCC Order No. R-2538

Approved, 19	Shell Oil Coppany
Except as follows:	Company or Operator
	ByR. A. Lowery Original Signed B# B. A. LOWERY
	Position District Exploitation Engineer
Approved OIL CONSERVATION COMMISSION	Send Communications regarding well to:
OIL CONSERVATION COMMISSION	
By	NameShell Oil Company
	Par 1959 Parcell New Marries
Tille	Address