

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PERORATION OFFICE	
OPERATOR	

(Form C-102)  
(Revised 7/1/62)

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

## MISCELLANEOUS NOTICES

MAR 9 9 03 AM '64

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be furnished to the Bureau on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	Convert To Dual Injection Well

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Roswell, New Mexico

March 4, 1964

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company

East Pearl-Queen Unit

Well No. ~~3420~~ 49 in. J

(Company or Operator)

Lease

(Unit)

NW 1/4 SE 1/4 of Sec. 34, T. 19 S, R. 35 E, NMPM., Pearl-Queen Pool  
(40-acre Subdivision)  
Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull rods, pump and tubing.
2. Perforate Zone IIA at 4880-4881' with two JSPF;  
IIIA at 4948-4950' with two JSPF;  
IIIB at 4956-4958' with two JSPF.
3. Run tubing with packer and set packer at 4800'. Test for communication.
4. Set packer at 4942' and treat below packer with 500 gallons 15% Fe NEA.
5. Pull tubing with packer.
6. Set permanent packer at 4800'.
7. Run 1 1/2" plastic coated tubing with dual packer spaced to set at 4735' with 2" plastic coated tubing below packer with seal assembly. Set packer.
8. Run 1 1/2" plastic coated tubing with seal assembly.
9. Hook up plastic coated well head and start injecting.

NMOCC Order No. R-2538

Approved....., 19.....  
Except as follows:

Shell Oil Company

Company or Operator

By..... R. A. Lowery Original Signed By

Position..... District Exploitation Engineer

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name..... Shell Oil Company

Title.....

Address..... Box 1858 Roswell, New Mexico