

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico
(Place)

December 30, 1960
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company Record Well No. 5 in B
(Company or Operator) (Unit)
NW 1/4 NE 1/4 of Sec. 35, T. 19 S., R. 35 E. NMPM, Pearl Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull rods and pump.
2. Circulate and fill casing with mud (properties shown in item #6).
3. Pull tubing.
4. Run casing free-point indicator (estimated cement top between 3400' and 3600').
5. Cut and pull casing.
6. Run tubing, circulate and condition mud to Wt. of 8.5 lbs/gal or more with viscosity of 30 seconds or more.
7. Spot 50 sxs neat cement (Class "C") over top of casing fish.
8. Spot 50 sxs neat cement (Class "C") at top of Yates from 3375' to 3425'.
9. Spot 50 sxs neat cement (Class "C") at top of Rustler Anhy. between 1725' and 1775'.
10. Spot 50 sxs neat cement (Class "C") at surface casing point between 85' and 135'.
11. Cap well with 5 sxs (Class "C") cement and erect prescribed 4" x 4' marker.

C/BP@4750

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Shell Oil Company

Company or Operator

ORIGINAL SIGNED BY

By R. L. Elkins

R. L. ELKINS

Position Division Mechanical Engineer

Send Communications regarding well to:

Name Shell Oil Company

Address Box 845 Roswell, New Mexico