

## NEW MEXICO OIL CONSERVATION COMMISSION

FORM C-103  
(Rev 3-55)

## MISCELLANEOUS REPORTS ON WELLS

HOBBS OFFICE 000

(Submit to appropriate District Office as per Commission Rule 1106)

Name of Company <b>C. W. TRAINER</b>		Address <b>P. O. Box 2222, Hobbs, New Mexico</b>				
Lease <b>Jordan</b>	Well No. <b>1</b>	Unit Letter <b>H</b>	Section <b>11</b>	Township <b>20-South</b>	Range <b>35-East</b>	
Date Work Performed <b>5/30-6/2-'60</b>	Pool <b>Wildcat</b>			County <b>Lea</b>		
THIS IS A REPORT OF: (Check appropriate block)						
<input type="checkbox"/> Beginning Drilling Operations		<input type="checkbox"/> Casing Test and Cement Job		<input type="checkbox"/> Other (Explain):		
<input checked="" type="checkbox"/> Plugging		<input type="checkbox"/> Remedial Work				
Detailed account of work done, nature and quantity of materials used, and results obtained.  <b>This well was plugged and abandoned as follows:</b>  <ol style="list-style-type: none"><li>1. 40 sack cement plug from 4680'-5034'</li><li>2. 15 sack cement plug from 4220'-4260'</li><li>3. Shot off and pulled 5½" casing from 3360'</li><li>4. 15 sack cement plug in and out of 5½" casing stub</li><li>5. 15 sack cement plug at 1950' (in Rustler Anhydrite)</li><li>6. 15 sack cement plug in and out of 10 3/4" surface casing set at 220'</li><li>7. 10 sack cement plug at surface</li><li>8. Erect 4" X 8' stenciled marker</li><li>9. Location has been cleaned and leveled and is ready for inspection.</li></ol>						
Witnessed by <b>C. W. Trainer</b>		Position <b>Owner-Operator</b>		Company <b>C. W. TRAINER</b>		
FILL IN BELOW FOR REMEDIAL WORK REPORTS ONLY						
ORIGINAL WELL DATA						
D F Elev.	T D	P B T D		Producing Interval		Completion Date
Tubing Diameter		Tubing Depth		Oil String Diameter		Oil String Depth
Perforated Interval(s)						
Open Hole Interval				Producing Formation(s)		
RESULTS OF WORKOVER						
Test	Date of Test	Oil Production BPD	Gas Production MCFPD	Water Production BPD	GOR Cubic feet/Bbl	Gas Well Potential MCFPD
Before Workover						
After Workover						
OIL CONSERVATION COMMISSION				I hereby certify that the information given above is true and complete to the best of my knowledge.		
Approved by <i>Leslie A. Clement</i>				Name <i>C. W. Trainer</i>		
Title				Position <b>C. W. Trainer Owner - Operator</b>		
Date				Company <b>C. W. TRAINER</b>		



**LTR**



**Job separation sheet**

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

May 24, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

C. W. TRAINER Jordan Well No. 1 in H  
(Company or Operator) (Lease) (Unit)  
SE 1/4 NE 1/4 of Sec. 11, T-20S, R-35E, NMPM, Wildcat Pool  
(40-acre Subdivision)  
Lea County.

### FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to plug and abandon this well as follows:

1. 40 sack cement plug from 4680'-5034'.
2. Pull 5½" casing from 3390' - Top of Cement.
3. 15 sack plug in and out of 5½" casing stub.
4. 15 sack plug at 1950' (in Rustler Anhydrite).
5. 15 sack plug in and out of 10 3/4" surface casing set at 220'.
6. 10 sack plug at surface.
7. Erect 4" X 8' stenciled marker.
8. Clean location.

MAY 25 1960

Approved....., 19.....  
Except as follows:.....

Approved.....  
OIL CONSERVATION COMMISSION

By.....  
Title.....

C. W. TRAINER  
Company or Operator

By.....  
Position.....  
Send Communications regarding well to:

Name.....  
Address.....