

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

August 7, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sinclair Oil & Gas Company State **600** Well No. **2** in **B**
(Company or Operator) Lease (Unit)
N $\frac{1}{4}$ **N** $\frac{1}{4}$ of Sec. **25**, T. **20S**, R. **35E**, NMPM., **Emery** Pool
(40-acre Subdivision)
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 4100'- Set 5 1/2" OD Casing @ 4100' Cemented w/ 100 Sk. - Top cement behind Casing @ 3496'
Run Electric log before and after setting casing
Perforated Casing f/ 4048 to 4060' w/ 48 jet shots-
Fractured w/ 20,000 Gal. refined oil & 20,000# Sand
Recovered all salt water after fracturing- did not recover 432 Bbl. load oil
Propose to set 10 sack cement plug f/ 3990' to 4090' after filling hole w. heavy mud
" to part & pull 5 1/2" OD Casing at approximately 3500' & set 10 Sk. cement plug from
3450 to 3550'- Set 25 Sk. cement plug from 2105 to 2025' (top Salt) and 25 Sk.
cement plug from 260 to 304' (bottom of surface casing (8 5/8" OD) - Set 4"
"Regulation Marker" in Top of 8 5/8" OD Casing & Bottom of Celler in 15 Sk. Cement
extending 4' above surface level- Fill cellar & pits & level location.

Approved....., 19.....
Except as follows:

Sinclair Oil & Gas Company
Company or Operator

By.....

Position.....
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Name.....**C. C. Salter, 520 E. Broadway, Hobbs, N.M.**

Title.....

Address.....