

RI AD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1804 feet, and from feet to feet.
Cable tools were used from 1804 feet to 5002 feet, and from feet to feet.

PRODUCTION

Put to Producing Dry Hole, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; 100% % water; and % was sediment. A.P.I.
Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
			Drillers Logs		
T. Anhy.	1875		T. Devonian		T. Ojo Alamo
T. Salt	2065		T. Silurian		T. Kirtland-Fruitland
B. Salt	3600		T. Montoya		T. Farmington
T. Yates	4015		T. Simpson		T. Pictured Cliffs
T. 7 Rivers	4130		T. McKee		T. Menefee
T. Queen			T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres			T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	90	90	Calechi - Sand	4130	4140		Soft Lime - HF Sulphur water
90	155	65	Red bed				
155	1070		Red bed	4140	5002		Lime
1070	1485		Sand				TD - Run electric log & Plugged & abandoned
1485	1800		Red rock - Red Sand				Filled hole mud laden fluid & Spotted cement plugs
1800	1804		Anhydrite - Landed 8-5/8"				20 sax
1804	1810		Change to Cable tools	5002	4902		
1810	1875		Anhydrite				
1875	2030		Red rock & shale	4350	4250		20 sax - Pulled 7" casing
2030	2065		Anhydrite	3750	3650		20 sax
2065	3600		Red rock & Anhydrite				
3600	3890		Salt - Potash & Anhydrite breaks	1925	1825		20 sax - Pulled 8-5/8 csg.
3890	3955		Lime & Anhydrite	200	175		20 sax
3955	3990		Anhydrite - Sand & Shale				
3990	4025		Lime				10 sax plug in top surface casing with 4" pipe marker installed.
4025	4130		Sand - 350' WIH				
			Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 7, 1957 (Date)

Company or Operator CACTUS DRILLING COMPANY

Address P.O. Box 788, San Angelo, Texas

Name

Position or Title Office Manager