N₋ ✓ MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

		Indicate Nature of	l Notice by Checki	ng Below	
NOTICE OF INTENTION O CHANGE PLANS		Notice of Intenti Temporarily Aban		Notice of Intention to Drill Deeper	
Notice of Intention o Plug Well	x	Notice of Intention of Plug Back	on	Notice of Intention to Set Liner	
lotice of Intention o Squeeze		Notice of Intention of Acidize	ON	Notice of Intention to Shoot (Nitro)	
OTICE OF INTENTION O GUN PERFORATE		Notice of Intentic (Other)	on	NOTICE OF INTENTION (OTHER)	
IL CONSERVATION CON ANTA FE, NEW MEXICO		San Angel	lo,Texas	7-31-57 (Date)	
entlemen:				,,	
Following is a Notice of	Intention to do	Certain work as descr	ribed below at the	CACTUS DRILLING COMPANY	
(Com	ipany or Operator)	Leese		A(Unit)
(40-acre Subdivision)	of Sec30	, T20	., R35,NA	СРМ.,	I
***************************************	Cov	inty.			
				ND REGULATIONS)	
coment plug on b	ottom, pul	ll 7" casing m	r gas; ran el udded at 4353	ectric log. Will place 2	20 sack led at
coment plug on b	ottom, pul e with muc	ll 7" casiny m i laden fluid a	r gas; ran el udded at 4353	ectric log. Will place 2	20 sack led at
coment plug on b	ottom, pul e with muc 43	ll 7" casing m i laden fluid a 353 4253	r gas; ran el udded at 4353	ectric log. Will place 2	20 sack led at
coment plug on b	ottom, pul e with mud 43 44	ll 7" casiny m i laden fluid a	r gas; ran el udded at 4353	ectric log. Will place 2	20 sack led at
coment plug on b	ottom, pul e with muc 43 46 37	ll 7" casing m i laden fluid a 353 4253 300 3900 750 3650 225 1825	r gas; ran el udded at 4353	ectric log. Will place 2	20 sack led at
cement plug on b 1804°. Fill hole	ottom, pul e with muc 43 46 37	ll 7" casing m i laden fluid s 353 4253 300 3900 750 3650 225 1825 200 125	r gas; ran el udded at 4353 and spot ceme	ectric log. Will place 2 st., and 8-5/8" casing muddent plugs as follows:	20 sack led at
coment plug on b	ottom, pul e with muc 43 46 37	ll 7" casing m i laden fluid s 353 4253 300 3900 750 3650 225 1825 200 125	r gas; ran el udded at 4353 and spot ceme	ectric log. Will place 2 st., and 8-5/8" casing muddent plugs as follows:	20 sack led at
cement plug on b 1804'. Fill hole	ottom, pul e with muc 43 46 37	ll 7" casing m i laden fluid s 353 4253 300 3900 750 3650 225 1825 200 125	r gas; ran el udded at 4353 and spot ceme	ectric log. Will place 2 st., and 8-5/8" casing muddent plugs as follows:	20 sack led at
cement plug on b 1804'. Fill hole	ottom, pul e with muc 43 46 37	ll 7" casing m i laden fluid s 353 4253 300 3900 750 3650 225 1825 200 125	r gas; ran el udded at 4353 and spot ceme	ectric log. Will place 2 st., and 8-5/8" casing muddent plugs as follows:	20 sack led at
cement plug on b 1804°. Fill hole	ottom, pul e with muc 43 46 37	ll 7" casing m i laden fluid s 353 4253 300 3900 750 3650 225 1825 200 125	r gas; ran el udded at 4353 and spot ceme	ectric log. Will place 2 st., and 8-5/8" casing muddent plugs as follows:	20 sack led at
will place cemen	ottom, pul e with muc 43 46 37 15 t cap and	11 7" casing m i laden fluid a 353 4253 300 3900 750 3650 325 1825 320 125 4" pipe marker	r gas; ran el udded at 4353 and spot ceme	ectric log. Will place 2 st., and 8-5/8" casing muddent plugs as follows:	20 sack led at
will place cemen	ottom, pul e with muc 43 46 37 15 t cap and	11 7" casing m i laden fluid a 353 4253 300 3900 750 3650 325 1825 320 125 4" pipe marker	r gas; ran el udded at 4353 and spot ceme	ectric log. Will place 2 st., and 8-5/8" casing muddent plugs as follows:	20 sack led at
will place cemen	ottom, pul e with muc 43 46 37 15 t cap and	11 7" casing m i laden fluid a 353 4253 300 3900 750 3650 325 1825 320 125 4" pipe marker	r gas; ran eludded at 4353 and spot ceme	ectric log. Will place 2. 1. and 8-5/8" casing muddent plugs as follows: tus Drilling Company Company of Operator	led at
will place cemen	ottom, pul e with muc 43 46 37 15 t cap and	11 7" casing m i laden fluid a 353 4253 300 3900 750 3650 325 1825 320 125 4" pipe marker	r gas; ran eludded at 4353 and spot ceme	ectric log. Will place 2. 1. and 8-5/8" casing muddent plugs as follows:	led at
will place cements pproved	ottom, pul e with muc 43 46 37 15 t cap and	11 7" casing m i laden fluid a 353 4253 300 3900 750 3650 325 1825 320 125 4" pipe marker	r gas; ran eludded at 4353 and spot ceme	ectric log. Will place 2. 1. and 8-5/8" casing muddent plugs as follows: tus Drilling Company Company of Operator	led at

Address Box 788. San Angelo, Texas