

RECORD OF DRILL-STEM AND SPECIAL TESTS

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEY WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO Maximum deviation 2 degrees by Totco at 2700.

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 4308 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM 1:13 FEET TO FEET.

PRODUCTION

PUT TO PRODUCING 6-17, 19 56
OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 38.64 BARRELS OF LIQUID OF WHICH 86 %
WAS OIL; % WAS EMULSION; 11 % WATER; AND % WAS
SEDIMENT. A.P.I. GRAVITY 27.6

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO		NORTHWESTERN NEW MEXICO	
T. ANHY	1173	T. DEVONIAN	
T. SALT	1630	T. SILURIAN	
B. SALT	2773	T. MONTOYA	
T. YATES	2922	T. SIMPSON	
T. 7 RIVERS	3214	T. McKEE	
T. QUEEN	3893	T. ELLENBURGER	
T. GRAYBURG		T. GR. WASH.	
T. SAN ANDRES		T. GRANITE	
T. GLORIETA		T.	
T. DRINKARD		T.	
T. TUBBS		T.	
T. ABO		T.	
T. PENN		T.	
T. MISS		T.	

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1173	1173	Red beds				
1173	1630	157	Anhydrite.				
1630	2773	1143	Salt, red shale.				
2773	2922	149	Red shale.				
2922	3214	322	Sand, anhydrite, shale.				
3214	3893	649	Dolomite, red shale.				
3893	4308	415	Sand, shale, anhydrite. & dolomite.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

July 21, 1956

COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Box 2347, Hobbs, New Mexico (DATE)
NAME M. M. Rogers POSITION OR TITLE Agent