



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

John M. Kelly Box 5671, Roswell, New Mexico
Company or Operator Address
Phillips State Well No. 1 in SESE of Sec. 12, T. 19S
Lease
R. 36E, N. M. P. M., Wildcat Field, Lea County.
Well is 4620 feet south of the North line and 660 feet west of the East line of Section 12
If State land the oil and gas lease is No. B-10233 Assignment No.
If patented land the owner is. Address.
If Government land the permittee is. Address.
The Lessee is. Phillips Petroleum Company Address.
Drilling commenced 12/17 1952 Drilling was completed 2/13 1953
Name of drilling contractor Rodgers, Inc. Address Hobbs, New Mexico
Elevation above sea level at top of casing 3733 feet.
The information given is to be kept confidential until 19.

OIL SANDS OR ZONES

No. 1, from 3650 to 3848 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 180 to 200 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
9 5/8	36	8	s	295	Texas				
7	20	8	s	3490	Larkin				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
12 3/4	9 5/8	295	200	Halliburton		
8 3/4	7	3490	400	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4100 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 2/13 1953
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours 3125 MCF Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in. 1200 #

EMPLOYEES

Baskin Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this Roswell 3/1/53
day of 19 Name John M. Kelly
Position Operator
Representing John M. Kelly
Company or Operator
My Commission expires Address Box 5671, Roswell, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	1015	1015	Red Beds and Gyp
1015	1722	707	Anhy. and gyp
1722	2658	836	Salt
2658	2964	306	Gyp & Anhy.
2964	3610	646	Lime
3610	3850	240	Sand & Sandy Lime
3850	4170	320	Sandy lime and lime