

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in duplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL			
NOTICE OF INTENTION TO DEEPEN WELL		NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>

Hobbs, New Mexico

Jan. 16, 1942

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

**Skelly Oil Company** - **Monstate** Well No. **3** in **CNW NW**  
Company or Operator Lease

of Sec. **13**, T. **19**, R. **36**, N. M. P. M., **Monstate** Field,  
**Lee** County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

This well, being a wildcat location, has been drilled to total depth of 4492', and in drilling from 4460' to 4480' a substantial amount of sulphur water was encountered. In drilling well all possibilities were checked very thoroughly, but no oil stains showed up in samples nor drilling fluid. In view of the fact that water had been encountered, as indicated above, and there being no possible oil pay in well, it is our intention, upon your approval, to plug and abandon this well in accordance with the rules and regulations of the New Mexico Oil Conservation Commission. The hole shall be loaded with mud-laden and a cement cap of approximately 10 sacks shall be put on top of this. The cellar shall then be filled and a joint of 4½" OD pipe shall be cemented in center of drilled hole with approximately 4' extending above surface to indicate location of the dry hole.

A cement plug shall be placed above the point where the sulphur water was encountered - hole below and above being loaded with mud-laden fluid, as indicated above.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

JAN 17 1942

OIL CONSERVATION COMMISSION

By Roy Yarbrough

OIL &amp; GAS INSPECTOR

Title \_\_\_\_\_

By J. R. DunawayPosition District Supt.

Send communications regarding well to

Name Skelly Oil Co.Address Hobbs, New Mexico

TABLE 1

WOLFE, D. 1992. *Journal of Great Lakes Research* 18:1-12.

[illegible]