

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B1431	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name State "T"
3. Address of Operator Drawer D, Monument, New Mexico 88265		9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>19S</u> RANGE <u>36E</u> NMPM.		10. Field and Pool, or Wildcat Eunice Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3628' DF		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

September 17 to September 25, 1980 - Pulled rods & pump, checked top of fill in open hole at 3930', pulled tbg. Cleaned out fill to 3939' w/sand pump. McCullough string shot G/SA zone in open hole fr. 3808' to 3939' w/300 gpf & w/500 gpf. Cleaned out fill fr. 3927' to 3939' w/sand pump. Ran pkr. & tbg. & set pkr. at 3754'. Pressure tested tbg. to 2000#. Held OK. Loaded 6-5/8" csg. w/2% KCl water & pressured to 500#. Acid Engineering acidized G/SA zone in open hole fr. 3808' to 3939' w/3500 gal. 15% NE-FE acid & 1000 gal. 20# gel in stages & flushed w/2% KCl water. Swabbed load. Pulled tbg. & pkr. & re-ran tbg., pump & rods & resumed pumping.

Test of 10-1-80: Pumped 60 b.o. & 75 b.w. in 24 hrs. on 13-52" SPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. B. Fisher TITLE Supv. Adm. Ser. DATE 10-2-80

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL [Signature]