## NEV IEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

### **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

OTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTE	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL		
OTICE OF INTENTION TO CHANGE PLANS		NTION TO PULL OR		
TICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL		
OTICE OF INTENTION TO DEEPEN WELL				
Monument, New E	exico	May 31, 1936		
L CONSERVATION COMMISSION.	Place	Date		
nta Fe, New Mexico.				
entlemen:				
ollowing is a notice of intentiton to do certain work as	described below at the			
merada Petroleum Corporation Company or Operator Lease	State was Well	No. 1 in SEL SEL		
Sec. 25 , T. 19 , R. 36	_, N. M. P. M., Mon	ment Field		
Lea County,	^			
FULL DETAILS OF PR	OLOSED LUAN OL M	ORK		
amounted her the Malliburger Mathed with	THE CONTROL HED BO	in this well at 2484' a		
cemented by the Halliburton Method with Casing and fittings wall be tested	### 1200# pump p	at. ressure and allowed to sta		
Casing and fittings wall be tested undistrubed for thirtymminutes. If no doe drilled out of casing and the same to bed for thirty minutes. If no drop in p	with 1200# pump prirop in pressure rest again applied	ressure and allowed to standard to the standard to standard undirect to		
Casing and fittings wall be tested undistrubed for thirtymminutes. If no doe drilled out of easing and the same to bed for thirty minutes. If no drop in p	with 1200# pump prirop in pressure rest again applied	ressure and allowed to standard to the standard to standard undirect to		
Casing and fittings wall be tested indistrubed for thirtymminutes. If no doe drilled out of easing and the same to sed for thirty minutes. If no drop in presumed.	with 1200# pump prirop in pressure rest again applied	ressure and allowed to standard to the standard to standard undirect to		
Casing and fittings wall be tested undistrubed for thirtymminutes. If no doe drilled out of casing and the same to sed for thirty minutes. If no drop in presumed.	with 1200# pump prirop in pressure rest again applied operative results the	ressure and allowed to state sults then the cement will and allowed to stand undir nen drilling will be		
Casing and fittings will be tested indistrubed for thirtynminutes. If no doe drilled out of casing and the same to sed for thirty minutes. If no drop in presumed.	with 1200# pump prirop in pressure rest again applied operative results the	ressure and allowed to standard to standard allowed to stand undirect design of the standard and standard will be		
Casing and fittings will be tested indistrubed for thirtynminutes. If no doe drilled out of casing and the same to sed for thirty minutes. If no drop in presumed.	with 1200# pump prirop in pressure rest again applied operative results the	ressure and allowed to state sults then the cement will and allowed to stand undir nen drilling will be		
Casing and fittings will be tested indistrubed for thirtymminutes. If no deed for thirtyminutes. If no deed for thirty minutes. If no drop in pesumed.	with 1200# pump prirop in pressure rest again applied apressure results the system of	ressure and allowed to state sults then the cement will and allowed to stand undir nen drilling will be		
Casing and fittings will be tested indistrubed for thirtynminutes. If no doe drilled out of casing and the same to sed for thirty minutes. If no drop in presumed.	with 1200# pump prirop in pressure rest again applied apressure results the pressure results	ressure and allowed to standard allowed to stand undirect desired allowed to stand undirect desired and allowed to stand undirect desired allowed to standard undirect desired allowed to stand undirect desired allowed to standard undire		
Casing and fittings wall be tested indistrubed for thirtynminutes. If no doe drilled out of casing and the same to sed for thirty minutes. If no drop in presumed.	with 1200# pump price in pressure rest again applied a pressure results the pressure results	ressure and allowed to standard allowed to stand undirect desired and allowed to standard undirect desired and allowed to stand undirect		
Casing and fittings wall be tested indistrubed for thirtynminutes. If no doe drilled out of casing and the same to be for thirty minutes. If no drop in presumed.	with 1200# pump price in pressure rest again applied a pressure results the pressure results	colsum Corporation Company or Operator  Boss  Countries and allowed to stand undirected and al		

# 

## and the second of the second

, Ç		***	•	ž.,		
					1.5 (1.5) 1.5)	ng ataon is
						٠
	•	•				